

Package: numOSL (via r-universe)

September 16, 2024

Type Package

Title Numeric Routines for Optically Stimulated Luminescence Dating

Version 2.8

Date 2023-12-06

Author Jun Peng [aut, cre], Bo Li [aut], Chunxin Wang [aut], Jorge More [ctb], Burton Garbow [ctb], Kenneth Hillstrom [ctb], John Burkardt [ctb], Paul Gilbert [ctb], Ravi Varadhan [ctb]

Maintainer Jun Peng <pengjun10@mails.ucas.ac.cn>

Description Optimizing regular numeric problems in optically stimulated luminescence dating, such as: equivalent dose calculation, dose rate determination, growth curve fitting, decay curve decomposition, statistical age model optimization, and statistical plot visualization.

License GPL-3

Depends R (>= 2.15.3)

Imports graphics, stats, utils, grDevices

URL <https://CRAN.R-project.org/package=numOSL>

NeedsCompilation yes

Date/Publication 2023-12-06 12:20:02 UTC

Repository <https://pengjunucas.r-universe.dev>

RemoteUrl <https://github.com/cran/numOSL>

RemoteRef HEAD

RemoteSha edb476d57ecab515a0166ccdbb6e6a7a5695a506

Contents

numOSL-package	2
analyseBINdata	3
as_analyseBIN	7
BIN	8

calDA	9
calED	13
calRcyRcp	17
calSARED	18
calSGCED	20
dbED	23
decomp	24
EDdata	27
fastED	28
fitGrowth	32
loadBINdata	35
lsNORM	37
mcFMM	39
mcMAM	41
optimSAM	42
pickBINdata	44
pickSARdata	46
psRadialPlot	48
RadialPlotter	49
reportMC	52
SARdata	53
scaleSGCN	54
sensSAM	56
Signaldata	57
Index	58

numOSL-package	<i>Package for tackling basic numeric problems in optically stimulated luminescence dating</i>
----------------	--

Description

Package for routine numeric optimization and data visualization in optically stimulated luminescence dating.

Details

Package: numOSL
 Type: Package
 Version: 2.8
 Date: 2023-12-06
 License: GPL-3

Author(s)

Jun Peng Hunan University of Science and Technology (HNUST), Xiangtan, China
Bo Li University of Wollongong (UOW), Wollongong, Australia
Chunxin Wang University of Science and Technology of China, Hefei, China

Package maintainer

Jun Peng <pengjun10@mails.ucas.ac.cn>

Related package projects

R program KMS <https://github.com/pengjunUCAS/KMS>

R package tgcd <https://CRAN.R-project.org/package=tgcd>

References

Peng J, Dong ZB, Han FQ, Long H, Liu XJ, 2013. R package numOSL: numeric routines for optically stimulated luminescence dating. *Ancient TL*, 31(2): 41-48.

Peng J, Li Bo, 2017. Single-aliquot Regenerative-Dose (SAR) and Standardised Growth Curve (SGC) Equivalent Dose Determination in a Batch Model Using the R Package 'numOSL'. *Ancient TL*, 35(2): 32-53.

analyseBINdata

BIN data analysis

Description

Analysing signal data records extracted from a BIN file.

Usage

```
analyseBINdata(obj_pickBIN, nfchn, nlchn, bg = "late",  
               me = 2.0, distp = "p", kph = NULL,  
               kdc = NULL, dcr = NULL, FR.fchn = NULL,  
               FR.mchn = NULL, FR.lchn = NULL,  
               signal.type = "LxTx", outfile = NULL)
```

```
analyseBINdata0(obj_pickBIN, fchn, lchn, bg="late", me=2.0,  
                distp="p", kph=NULL, kdc=NULL, dcr=NULL,  
                FR.fchn=NULL, FR.mchn=NULL, FR.lchn=NULL,  
                signal.type="LxTx", outfile=NULL)
```

Arguments

obj_pickBIN **list(required)**: an object of S3 class "pickBIN" produced by function [pickBINdata](#)

nfchn	integer(required) : number of the first few channels from the initial part of a decay curve. Number of counts summed over channels $(\text{Delay}+1L) : (\text{Delay}+\text{nfchn})$ is calculated as the fast-component plus background signal
n1chn	integer(required) : number of the last few channels from the latter part of a decay curve. If <code>bg="late"</code> , number of counts averaged over channels $(\text{Delay}+0n-\text{n1chn}+1L) : (\text{Delay}+0n)$ will be calculated as the background signal, if <code>bg="early"</code> , number of counts averaged over channels $(\text{Delay}+\text{nfchn}+1L) : (\text{Delay}+\text{nfchn}+\text{n1chn})$ will be calculated as the background signal. Delay and 0n are obtained internally from the BIN file.
fchn	integer(required) : channels used for calculating the fast-component signals
lchn	integer(required) : channels used for calculating the background counts
bg	character(with default) : background subtraction method, i.e., <code>bg="early"</code> or <code>bg="late"</code>
me	numeric(with default) : measurement error of Lx (or Tx) in percent
distp	character(with default) : distribution of photon counts, <code>distp="p"</code> denotes Poisson distribution, <code>distp="op"</code> denotes Over Poisson distribution
kph	numeric(optional) : correction factor for photon counts
kdc	numeric(optional) : correction factor for dark counts
dcr	numeric(optional) : dark count rate
FR.fchn	vector(optional) : fast-component signal channels, note that those channels are extracted internally from the "ON" channels, i.e., <code>FR.fchn=((Delay+1):(Delay+0n))[FR.fchn]</code> . Example: <code>FR.fchn=1:5</code>
FR.mchn	vector(optional) : medium-component signal channels, note that those channels are extracted internally from the "ON" channels, i.e., <code>FR.mchn=((Delay+1):(Delay+0n))[FR.mchn]</code> . Example: <code>FR.mchn=31:60</code>
FR.lchn	vector(optional) : background signal channels, note that those channels are extracted internally from the "ON" channels, i.e., <code>FR.lchn=((Delay+1):(Delay+0n))[FR.lchn]</code> . Example: <code>FR.lchn=201:250</code>
signal.type	character(with default) : type of signal, "LxTx", "Lx", or "Tx"
outfile	character(optional) : if specified, analysis results (i.e., NO, Position, Grain, SAR.Cycle, Dose, Init, BG, Lx, seLx, TInit, TBG, Tx, seTx, LxTx, seLxTx) will be written to a CSV file named "outfile" and saved to the current work directory

Details

Function `analyseBINdata` is used for signal (i.e., Lx, Tx, and Lx/Tx) calculation. It provides two protocols for background subtraction (i.e., the early and late background subtraction methods).

Standard error of signals are assessed using two methods: if photon counts are assumed to follow Poisson distributions, **Eqn.(3)** of Galbraith (2002) will be applied; if photon counts are over-dispersed, **Eqn.(10)** of Bluszcz et al. (2015) will be applied.

If arguments FR.fchn, FR.mchn, and FR.lchn are provided, fast ratio will be calculated according to Madsen et al. (2009).

Value

Return an invisible [list](#) of S3 class object "analyseBIN" containing the following elements:

SARdata	a data.frame containing calculated SAR data sets
criteria	values used as rejection criteria (0-1 values indicating if Tn is more than 3 sigma above BG or not, ratio of initial Tn signal to BG and associated standard error, relative standard error of Tn in percent, fast ratio of Tn and associated standard error), NA is produced if the value can not be calculated. Note that in this function rejection criteria are calculated but not applied
Tn	values of Tn and associated standard errors
LnTn.curve	decay curves for Ln and Tn for different aliquots (grains)
TxTn	ratios of Tx to Tn for various SAR cycles
agID	aliquot or grain ID (i.e., NO, Position, and Grain)

SARdata is a [data.frame](#) containing the following elements if `signal.type="LxTx"`:

Element	Description
NO	aliquot (grain) number
SAR.Cycle	SAR cycle (N, R1, R2, R3, ...)
Dose	regenerative dose
LxTx	sensitivity-corrected regenerative-dose signal
seLxTx	standard error of LxTx

SARdata contains the following elements if `signal.type="Lx"`:

Element	Description
NO	aliquot (grain) number
SAR.Cycle	SAR cycle (N, R1, R2, R3, ...)
Dose	regenerative dose
Lx	regenerative-dose signal
seLx	standard error of Lx

SARdata contains the following elements if `signal.type="Tx"`:

Element	Description
NO	aliquot (grain) number
SAR.Cycle	SAR cycle (N, R1, R2, R3, ...)
Dose	regenerative dose
Tx	test-dose signal

seTx standard error of Tx

Note

Though function [analyseBINdata](#) is originally designed to analyze CW-OSL data sets, IRSL data sets obtained from the SAR protocol can also be analyzed.

References

- Ballarini M, Wallinga J, Wintle AG, Bos AJJ, 2007. A modified SAR protocol for optical dating of individual grains from young quartz samples. *Radiation Measurements*, 42(3): 360-369.
- Bluszcz A, Adamiec G, Heer AJ, 2015. Estimation of equivalent dose and its uncertainty in the OSL SAR protocol when count numbers do not follow a Poisson distribution. *Radiation Measurements*, 81: 46-54.
- Cunningham AC, Wallinga J, 2010. Selection of integration time intervals for quartz OSL decay curves. *Quaternary Geochronology*, 5(6): 657-666
- Duller GAT, 2016. *Analyst* (v4.31.9), User Manual.
- Durcan JA, Duller GAT, 2011. The fast ratio: A rapid measure for testing the dominance of the fast component in the initial OSL signal from quartz. *Radiation Measurements*, 46(10): 1065-1072.
- Galbraith R, 2002. A note on the variance of a background-corrected OSL count. *Ancient TL*, 20(2): 49-51.
- Madsen AT, Duller GAT, Donnelly JP, Roberts HM, Wintle AG, 2009. A chronology of hurricane landfalls at Little Sippewissett Marsh, Massachusetts, USA, using optical dating. *Geomorphology*, 109(1-2): 36-45.

See Also

[loadBINdata](#); [pickBINdata](#); [pickSARdata](#); [calED](#);
[calSARED](#); [calSGCED](#); [fitGrowth](#); [lsNORM](#); [BIN](#)

Examples

```
### Example 1 (not run):
# obj_loadBIN <- loadBINdata("foo.bin", view=TRUE)
# obj_pickBIN <- pickBINdata(obj_loadBIN, Position=2, LType="OSL")
# analyseBINdata(obj_pickBIN, nfchn=3, nlchn=20)

### Example 2:
data(BIN)
obj_pickBIN <- pickBINdata(BIN, Position=c(2,4,6,8,10),
                           LType="OSL", view=FALSE)
obj_analyseBIN <- analyseBINdata(obj_pickBIN, nfchn=4, nlchn=20)
#obj_analyseBIN <- analyseBINdata0(obj_pickBIN, fchn=1:4, nlchn=231:250)
obj_analyseBIN$SARdata
```

as_analyseBIN *Transform SAR data sets into S3 class object "analyseBIN"*

Description

Transform SAR data sets into S3 class object "analyseBIN".

Usage

```
as_analyseBIN(SARdata)
```

Arguments

SARdata **matrix(required)**: SAR data set, it should contain five columns (i.e., NO, SAR.Cycle, Dose, Signal, and Signal.Err), see [SARdata](#) for details

Value

Return an invisible [list](#) of S3 class object "analyseBIN" containing the following elements:

SARdata	a data.frame containing SAR data sets
criteria	values used as rejection criteria, here it is set equal to NULL
Tn	values of Tn and associated standard errors, here it is set equal to NULL
LnTn.curve	decay curves of Ln and Tn for different aliquots (grains), here it is set equal to NULL
TxTn	ratios of Tx to Tn for various SAR cycles, here it is set equal to NULL
agID	aliquot or grain ID (i.e., NO, Position, and Grain), here both Position and Grain are set equal to 0

SARdata is a [data.frame](#) containing the following elements:

Element	Description
NO	aliquot (grain) number
SAR.Cycle	SAR cycle (N, R1, R2, R3, ...)
Dose	regenerative dose
Signal	OSL signal
Signal.Err	standard error of OSL signal

Note

Function [as_analyseBIN](#) transforms SAR data sets (see [SARdata](#)) into S3 class object "analyseBIN". The returned elements such as criteria, Tn, LnTn.curve, and TxTn are set equal to NULL.

See Also

[analyseBINdata](#); [SARdata](#); [calSARED](#); [pickSARdata](#)

Examples

```
### Example 1:
data(SARdata)
obj_analyseBIN <- as_analyseBIN(SARdata[1:8,,drop=FALSE])
res_calSARED <- calSARED(obj_analyseBIN)
res_calSARED$sarED

### Example 2 (not run):
# obj_analyseBIN <- as_analyseBIN(SARdata)
# res_calSARED <- calSARED(obj_analyseBIN, rcy1.range=c(1,1), outpdf="SARED")

### Example 3 (not run):
# obj_analyseBIN <- as_analyseBIN(SARdata)
# res_pickSARdata <- pickSARdata(obj_analyseBIN, fom.up=6, outpdf="SARdata")
# res_pickSARdata$SARdata
```

BIN

BIN data

Description

BIN data for aeolian sample GL2-1 from the south margin of the Tengger Desert (Peng et al., 2013).

Usage

```
data(BIN)
```

Format

A S3 class object "loadBIN" produced by function [loadBINdata](#) that contains the following two elements:

records a [list](#) consists of loaded data records for each aliquot (grain)

tab a [data.frame](#) used for summarizing loaded data records

References

Peng J, Han FQ, 2013. Selections of fast-component OSL signal using sediments from the south edge of Tengger Desert. *Acta Geoscientica Sinica*, 34(6): 757-762.

See Also

[loadBINdata](#); [pickBINdata](#); [analyseBINdata](#)

Examples

```
# Not run.
# data(BIN)
# class(BIN)
```

 calDA *Dose rate and age calculation*

Description

Calculating the total dose rate and burial age and assessing associated standard errors using a Monte Carlo method.

Usage

```
calDA(dose, minGrainSize, maxGrainSize,
      Ucontent, Thcontent, Kcontent, Rbcontent, Wct, depth, longitude,
      latitude, altitude, alphaValue = 0, inKcontent = 0, inRbcontent = 0,
      calRbfromK = FALSE, bulkDensity = 2.5, cfType = "Liritzis2013", rdcf = 0,
      rba = 0, ShallowGamma = TRUE, nsim = 5000, reject = TRUE, plot = TRUE,
      sampleName = "")

calDAbatch(inputfile = "inputDRtable", cfType = "Liritzis2013",
           rdcf = 0, rba = 0, calRbfromK = FALSE,
           ShallowGamma = TRUE, nsim = 5000, reject = TRUE,
           outfile = paste(inputfile, "_Results", sep=""),
           outpdf = paste(inputfile, "_Results", sep=""), digits = 4)
```

Arguments

dose	vector(required) : a two-element vector containing the equivalent dose and associated measurement error (unit, Gy)
minGrainSize	numeric(required) : lower limit on grain size (unit, um)
maxGrainSize	numeric(required) : upper limit on grain size (unit, um)
Ucontent	vector(required) : a two-element vector containing the uranium content and its measurement error (unit, ppm)
Thcontent	vector(required) : a two-element vector containing the thorium content and its measurement error (unit, ppm)
Kcontent	vector(required) : a two-element vector containing the potassium content and its measurement error (unit, percent)
Rbcontent	numeric(required) : the rubidium content (unit, ppm). The measurement error is optional
Wct	vector(required) : a two-element vector containing the water content and its measurement error (unit, percent)
depth	numeric(required) : sampling depth (unit, m). The associated error is optional
longitude	numeric(required) : longitude of the sampling site (unit, decimal degree). The associated error is optional
latitude	numeric(required) : latitude of the sampling site (unit, decimal degree). The associated error is optional

altitude	numeric(required) : altitude of the sampling site (unit, m above sea level). The associated error is optional
alphaValue	numeric (with default): average alpha efficiency. The associated error is optional, for example, alphaValue=0.038 or alphaValue=c(0.038,0.002)
inKcontent	numeric (with default): internal potassium content (unit, percent). The associated error is optional, for example, inKcontent=12.5, or inKcontent=c(12.5,0.5)
inRbcontent	numeric (with default): internal rubidium content (unit, ppm). The associated error is optional, for example, inRbcontent=400, or inRbcontent=c(400,100)
calRbfromK	logical (with default): whether calculate the rubidium and internal rubidium contents using the provided potassium and internal potassium contents respectively. If calRbfromK=TRUE, the provided rubidium and/or internal rubidium contents will not be used for dose-rate calculation
bulkDensity	numeric (with default): average density of bulk sample (unit, g/cm ³). The associated error is optional, for example, bulkDensity=2.5, or bulkDensity=c(2.5,0.2)
cfType	character (with default): type of the conversion factor, one from "AdamicAitken1998", "Guerin2011", and "Liritzis2013"
rdcf	numeric (with default): constant relative standard error (RSD) for dose-rate conversion factors (unit, percent). If rdcf=0, the dose-rate conversion factors will be assumed to be perfectly determined, otherwise their errors calculated using the constant RSD will be accounted for during the Monte Carlo simulation. Since the conversion factors of "Liritzis2013" contain measured standard errors, when cfType="Liritzis2013", a positive rdcf value indicates that the measured errors will be accounted for during simulation
rba	numeric (with default): constant RSD for alpha and beta dose absorption fractions (unit, percent). If rba=0, the determined alpha and beta dose attenuation factors will be assumed to be free from errors
ShallowGamma	logical (with default): consider the scaling of gamma dose rate for samples collected at shallow burial depths or not
nsim	integer (with default): number of Monte Carlo simulations
reject	logical (with default): whether randomly generated negative values of variables (including equivalent dose, uranium, thorium, potassium, and water contents, alpha efficiency, and bulk-sample density, etc) and meaningless values (longitude beyonds [-180, 180], or latitude beyonds [-90, 90]) will be reject during the Monte Carlo simulation
plot	logical (with default): draw a plot showing the simulated distributions of dose rates and ages or not
sampleName	character (with default): name of the sample
inputfile	character (with default): name of the input file containing measured dataset of individual samples used for dose rate and age calculations
outfile	character (with default): name of the files containing the results of calculated dose rates and ages for a number of samples. The files will be written using CSV/HTML format and saved to the current work directory

outpdf	character (with default): name of a PDF file showing the distributions of dose rates and ages simulated using a Monte Carlo method for a number of samples. The file will be saved to the current work directory
digits	integer (with default): the number of decimal places or significant digits to be used for values of the output CSV/HTML files

Details

Function **calDA** is used for calculating the annual dose rate and burial age using the concentrations of radioactive nuclides (uranium, thorium, potassium) obtained from Neutron Activation Analysis (NAA) or inductively coupled plasma mass spectrometry (ICP-MS), grain size, water content, average sample density, geographical parameters (depth, longitude, latitude, altitude), and the equivalent dose. The elemental concentrations of uranium, thorium, and potassium are converted into alpha, beta, and gamma dose rates according to dose-rate conversion factors (Adamiec and Aitken, 1998; Guerin et al., 2011; Liritzis et al., 2013). Alpha and beta dose absorbed fractions are determined using published data (Mejdahl, 1979; Brennan et al., 1991). The contribution of the internal beta dose rate can be assessed if the internal potassium content is provided. The gamma dose rate for samples collected at shallow depths are corrected using the scaling factors of Aitken (1985). The cosmic ray dose rate is estimated as a function of depth, altitude and geomagnetic latitude (Prescott and Hutton, 1994) and the contribution to cosmic dose rate from a soft component is considered at shallow depths (Barbouti and Rastin, 1983).

The hydrofluoric acid-etched quartz and K-feldspar samples have an alpha efficiency of zero, while the reported alpha values of un-etched coarse-grained quartz and K-feldspar are 0.1 ± 0.02 (Olley et al., 1998) and 0.15 ± 0.05 (Balescu and Lamothe, 1994), respectively. Three reported alpha values for fine-grained quartz are 0.038 ± 0.002 (Rees-Jones, 1995), 0.04 ± 0.01 (Rees-Jones and Tite, 1997), and 0.035 ± 0.003 (Lai et al., 2008). Two reported alpha values for fine-grained polymineral are 0.086 ± 0.004 (Rees-Jones, 1995) and 0.09 ± 0.02 (Kreutzer et al., 2014). Huntley and Hancock (2001) assumed an internal rubidium content of 400 ± 100 ppm. Three reported internal potassium contents are $12.5 \pm 0.5\%$ (Huntley and Baril, 1997), $13 \pm 1\%$ (Zhao and Li, 2005), and $10 \pm 2\%$ (Smedley et al., 2012).

The standard error of the age and dose rate is estimated by a "parametric bootstrap" method (Peng et al., 2016). Constant relative standard errors for dose-rate conversion factors, alpha and beta dose absorption factors can be assumed during the simulation. Arguments such as dose, Ucontent, Thcontent, Kcontent, Wct should be two-element vectors representing paired values of $\mu \pm \sigma$, where μ and σ denote the measured value and associated standard error, respectively. Arguments such as depth, longitude, latitude, altitude, alphaValue, Rbcontent, inKcontent, inRbcontent, and bulkDensity, can be either a scalar or a two-element vector. This means that uncertainties from these quantities can be either ignored or taken into account during the simulation.

Function **calDAbatch** is a wrapper of the function **calDA** and is used to calculate the dose rates and burial ages for a number of samples in a batch mode. The function requires as input a CSV file containing dose-rate datasets of different samples that are saved row by row. A template of the input CSV file with the name "myDRdata" can be generated using the command `calDAbatch("myDRdata")` (see examples).

Value

Function `calDA` returns a `matrix` that contains calculated alpha, beta, gamma, cosmic, and total dose rate and age and associated standard errors, lower and upper bounds of 95 percent confidence intervals for the sample under considered.

Function `calDABatch` returns an invisible `list` that contains calculated dose-rate results for each of the provided samples.

Author(s)

Original R code written by Jun Peng, improved version of code written by Chunxin Wang

References

- Adamiec G, Aitken M, 1998. Dose-rate conversion factors: update. *Ancient TL*, 16(2): 37-49.
- Aitken MJ, 1985. *Thermoluminescence Dating*. Academic Press, London.
- Balescu S, Lamothe M, 1994. Comparison of TL and IRSL age estimates of feldspar coarse grains from waterlain sediments. *Quaternary Science Reviews*, 13: 437-444.
- Barbouti AI, Rastin BC, 1983. A study of the absolute intensity of muons at sea level and under various thicknesses of absorber. *Journal of Physics G Nuclear Physics*, 9: 1577e1595.
- Brennan BJ, Lyons RG, Phillips SW, 1991. Attenuation of alpha particle track dose for spherical grains. *International Journal of Radiation Application and Instrumentation. Part D. Nuclear Tracks and Radiation Measurements*, 18: 249-253.
- Guerin G, Mercier N, Adamiec G, 2011. Dose-rate conversion factors: update. *Ancient TL*, 29: 5-8.
- Huntley DJ, Baril M, 1997. The K content of the K-feldspars being measured in optical dating or in thermoluminescence dating. *Ancient TL*, 15: 11-13.
- Huntley DJ, Hancock R, 2001. The Rb contents of the K-feldspar grains being measured in optical dating. *Ancient TL*, 19: 43-46.
- Kreutzer S, Schmidt C, DeWitt R, Fuchs M, 2014. The a-value of polymineral fine grain samples measured with the post-IR IRSL protocol. *Radiation Measurements*, 69: 18-29.
- Lai ZP, Zoller L, Fuchs M, Bruckner H, 2008. Alpha efficiency determination for OSL of quartz extracted from Chinese loess. *Radiation Measurements*, 43: 767-770.
- Liritzis I, Stamoulis K, Papachristodoulou C, Ioannides K, 2013. A re-evaluation of radiation dose-rate conversion factors. *Mediterranean Archaeology and Archaeometry*, 13: 1-15.
- Mejdahl V, 1979. Thermoluminescence dating: beta-dose attenuation in quartz grains. *Archaeometry*, 21: 61-72.
- Olley J, Caitcheon G, Murray A, 1998. The distribution of apparent dose as determined by Optically Stimulated Luminescence in small aliquots of fluvial quartz. Implications for dating young sediments. *Quaternary Science Reviews*, 17: 1033-1040.
- Prescott, JR, Hutton JT, 1994. Cosmic ray contributions to dose rates for Luminescence and ESR dating: large depths and long-term time variations. *Radiation Measurements*, 23(2-3): 497-500.
- Peng J, Dong ZB, Zhang ZC, 2016. Determining the error of dose rate estimates on luminescence dating using Monte Carlo approach. *Nuclear Techniques*, 38(7): 070201. (In Chinese).

Rees-Jones J, 1995. Optical dating of young sediments using fine-grained quartz. *Ancient TL*, 13: 9-14.

Rees-Jones J, Tite MS, 1997. Optical dating results for British archaeological sediments. *Archaeometry*, 39: 177-187.

Smedley RK, Duller GAT, Pearce NJG, Roberts HM, 2012. Determining the K-content of single-grains of feldspar for luminescence dating. *Radiation Measurements*, 47: 790-796.

Zhao H, Li SH, 2005. Internal dose rate to K-feldspar grains from radioactive elements other than potassium. *Radiation Measurements*, 40: 84-93.

Further reading

Durcan JA, King GE, Duller GAT, 2015. DRAC: Dose Rate and Age Calculator for trapped charge dating. *Quaternary Geochronology*, 28: 54-61.

Grun R, 2009. The "AGE" program for the calculation of luminescence age estimates. *Ancient TL*, 27: 45-46.

Examples

```
calDA(dose=c(25.04,0.68), minGrainSize=90,
      maxGrainSize=180, Ucontent=c(2.86,0.19),
      Thcontent=c(8.63,0.34), Kcontent=c(2.00,0.11), Rbcontent=0,
      Wct=c(0.05,0.05), depth=c(1.1,0.05), longitude=c(103.16,0.1),
      latitude=c(37.64,0.1), altitude=c(1170,58.5), bulkDensity=c(2.5,0.1),
      rdcf=0.03, rba=0.03)

# Not run.
# Generate a template of input CSV file "myDRdata" using the following command.
# calDAbatch(inputfile="myDRdata")

# Put your dose rate dataset into the above generated template file "myDRdata.csv", then run
# the following command to calculate dose rates and ages for your samples in a batch mode.
# d <- calDAbatch(inputfile="myDRdata", nsim=3000)
# idx <- sapply(d, is.matrix)
# h <- t(sapply(d[idx],function(x) c(t(x[6:7,1:2]))))
# colnames(h) <- c("DR", "Se.DR", "Age", "Se.Age")
# print(h)
```

Description

Calculating an equivalent dose and assessing its standard error.

Usage

```
calED(Curvedata, Ltx, model = "gok", origin = FALSE,
      errMethod = "sp", nsim = 500, weight = TRUE,
      trial = FALSE, plot = TRUE, nofit.rgd = NULL,
      agID = NULL, Tn = NULL, Tn3BG = NULL,
      TnBG.ratio = NULL, rseTn = NULL, FR = NULL,
      LnTn.curve = NULL, TxTn = NULL)
```

Arguments

Curvedata	matrix(required) : a three-column matrix (i.e., regenerative doses, sensitivity-corrected regenerative-dose signals, and associated standard errors)
Ltx	vector(required) : a two-element vector consists of sensitivity-corrected natural-dose signal and its error
model	character (with default): model used for growth curve fitting, see fitGrowth for available models
origin	logical (with default): logical value indicating if the growth curve should be forced to pass the origin
errMethod	character (with default): method used for equivalent dose error assessment. "sp" and "mc" denote error estimation using the Simple Transformation and Monte Carlo methods, respectively
nsim	integer (with default): desired number of randomly simulated equivalent dose obtained by Monte Carlo simulation
weight	logical (with default): logical value indicating if the growth curve should be fitted using a weighted procedure, see function fitGrowth for details
trial	logical (with default): logical value indicating if the growth curve should be fitted using other models if the given model fails, see function fitGrowth for details
plot	logical (with default): logical value indicating if the results should be plotted
nofit.rgd	integer (optional): regenerative doses that will not be used during the fitting. For example, if <code>nofit.rgd=1</code> then the first regenerative dose will not be used during growth curve fitting
agID	vector (optional): a three-element vector indicating aliquot (grain) ID, i.e., <code>agID[1]=NO</code> , <code>agID[2]=Position</code> , <code>agID[3]=Grain</code>
Tn	vector (optional): a two-element vector containing value and standard error of Tn
Tn3BG	numeric (optional): 0-1 value indicating if Tn is more than 3 sigma above BG, 1 indicates $Tn > 3_sigma_BG$, 0 indicates $Tn \leq 3_sigma_BG$
TnBG.ratio	vector (optional): a two-element vector containing value and standard error of ratio of initial Tn signal to BG
rseTn	numeric (optional): relative standard error of Tn in percent
FR	vector (optional): a two-element vector containing value and standard error of fast ratio of Tn
LnTn.curve	list (optional): decay curve data for Ln and Tn, it should contain four elements, i.e., <code>names(LnTn.curve)=c("Ln.x", "Ln.y", "Tn.x", "Tn.y")</code>
TxTn	vector (optional): ratios of Tx to Tn for various SAR cycles

Details

Function `calED` is used for calculating an equivalent dose and assessing its standard error. The standard errors of an equivalent dose can be assessed using the Simple Transformation or Monte Carlo method (Duller, 2007).

Interpolation is performed using a combination of golden section search and successive parabolic interpolation (**R** function `optimize` in package `stats`) (freely available Fortran 77 source code at <https://www.netlib.org/fmm/fmin.f>). See function `fitGrowth` for more details on growth curve fitting.

Value

Return an invisible `list` that contains the following elements:

<code>message</code>	return 0 if calculation succeeds, 1 if growth curve fitting fails, 2 if natural-dose signal saturates, 3 if equivalent dose calculation fails, 4 if equivalent dose error assessment fails
<code>fitIDX</code>	Indices of dose points used in growth curve fitting
<code>LMpars</code>	optimized parameters for the growth curve
<code>value</code>	minimized objective for the growth curve
<code>avg.error</code>	average fit error for the growth curve
<code>RCS</code>	reduced chi-square value for the growth curve
<code>FOM</code>	figure of merit value for the growth curve in percent
<code>calED.method</code>	method used for equivalent dose calculation, i.e., "Interpolation" or "Extrapolation"
<code>mcED</code>	randomly simulated equivalent doses
<code>ED</code>	calculated equivalent dose and its standard error
<code>ConfInt</code>	68 percent and 95 percent confidence intervals for the equivalent dose
<code>RecyclingRatio1</code>	the first recycling ratio and its standard error
<code>RecyclingRatio2</code>	the second recycling ratio and its standard error
<code>RecyclingRatio3</code>	the third recycling ratio and its standard error
<code>Recuperation1</code>	the first recuperation (i.e., ratio of the sensitivity-corrected zero-dose signal to natural-dose signal) and its standard error in percent
<code>Recuperation2</code>	the second recuperation (i.e., ratio of the sensitivity-corrected zero-dose signal to maximum regenerative-dose signal) and its standard error in percent

Note

Arguments `agID`, `Tn`, `Tn3BG`, `TnBG.ratio`, `rseTn`, `FR`, `LnTn.curve`, and `TxTn` have nothing to do with equivalent dose calculation. They are used only for plotting purpose.

Argument `Tn3BG` indicates if `Tn` (after background subtraction) is more than 3 sigma above `BG`, while argument `TnBG.ratio` denotes the ratio of `Tn` (no background subtraction) to `BG`.

Function `calED` will return `message=3` (i.e., "Failed in equivalent dose calculation") if the equivalent dose to be calculated below `-50` (<Gy>|<s>).

68 percent (one sigma) and 95 percent (two sigma) confidence intervals of equivalent doses will be determined respectively using normal approximation and Monte Carlo simulation, for `errMethod="sp"` and `errMethod="mc"`.

Function `sgcED` in previous versions was bundled to function `calSGCED`.

References

Duller GAT, 2007. Assessing the error on equivalent dose estimates derived from single aliquot regenerative dose measurements. *Ancient TL*, 25(1): 15-24.

Duller GAT, 2016. *Analyst* (v4.31.9), User Manual.

Galbraith RF, Roberts RG, 2012. Statistical aspects of equivalent dose and error calculation and display in OSL dating: an overview and some recommendations. *Quaternary Geochronology*, 11: 1-27.

See Also

[analyseBINdata](#); [fitGrowth](#); [calRcyRcp](#); [calSARED](#); [fastED](#); [calSGCED](#)

Examples

```
### Example 1:
Curvedata <- cbind(c(0, 18, 36, 54, 72, 0, 18),
                  c(0.026, 1.55, 2.39, 3.46, 4.13, 0.023, 1.61),
                  c(0.005, 0.11, 0.27, 0.22, 0.20, 0.008, 0.24))
Ltx <- c(3.1, 0.31)
calED(Curvedata, Ltx, model="exp", origin=FALSE)

### Example 2 (not run):
# data(BIN)
# obj_pickBIN <- pickBINdata(BIN, Position=48,
#                             LType="OSL", view=FALSE)
# obj_analyseBIN <- analyseBINdata(obj_pickBIN, nfchn=3, nlchn=20)
# Curvedata <- obj_analyseBIN$SARdata[-1,3:5]
# Ltx <- as.numeric(obj_analyseBIN$SARdata[1,4:5])
# calED(Curvedata, Ltx, model="gok", origin=FALSE)
```

calRcyRcp	<i>Recycling ratio and recuperation calculation</i>
-----------	---

Description

Calculating recycling ratio, recuperation, and associated standard errors.

Usage

```
calRcyRcp(Curvedata, Ltx)
```

Arguments

Curvedata	matrix(required) : a three-column matrix (i.e., regenerative doses, sensitivity-corrected regenerative-dose signals, and associated standard errors)
Ltx	vector(required) : a two-element vector consists of sensitivity-corrected natural-dose signal and its error

Value

Return a [list](#) that contains the following elements:

RecyclingRatio1	the first recycling ratio and its standard error
RecyclingRatio2	the second recycling ratio and its standard error
RecyclingRatio3	the third recycling ratio and its standard error
Recuperation1	the first recuperation (i.e., ratio of the sensitivity-corrected zero-dose signal to natural-dose signal) and its standard error in percent
Recuperation2	the second recuperation (i.e., ratio of the sensitivity-corrected zero-dose signal to maximum regenerative-dose signal) and its standard error in percent

Note

If the sensitivity-corrected signals for the first, second, and third repeated regenerative doses are R1, R2, and R3, respectively, then $\text{RecyclingRatio1} = R2/R1$, $\text{RecyclingRatio2} = R3/R1$, and $\text{RecyclingRatio3} = R3/R2$.

References

Wintle AG, Murray AS, 2006. A review of quartz optically stimulated luminescence characteristics and their relevance in single-aliquot regeneration dating protocols. *Radiation Measurements*, 41(4): 369-391.

See Also

[calED](#); [fastED](#); [calSARED](#); [pickSARdata](#)

calSARED

*SAR equivalent doses calculation and selection***Description**

Calculating and selecting a series of equivalent doses in a batch mode according to the single aliquot regenerative-dose (SAR) method (Murray and Wintle, 2000).

Usage

```
calSARED(obj_analyseBIN, model = "gok", origin = FALSE,
         errMethod = "sp", nsim = 500, weight = TRUE,
         trial = TRUE, nofit.rgd = NULL, Tn.above.3BG = TRUE,
         TnBG.ratio.low = NULL, rseTn.up = NULL, FR.low = NULL,
         rcy1.range = NULL, rcy2.range = NULL, rcy3.range = NULL,
         rcp1.up = NULL, rcp2.up = NULL, fom.up = NULL,
         rcs.up = NULL, calED.method = NULL, rseED.up = NULL,
         use.se = TRUE, outpdf = NULL, outfile = NULL)
```

Arguments

obj_analyseBIN	list(required) : an object of S3 class "analyseBIN" produced by function analyseBINdata or as_analyseBIN
model	character (with default): model used for growth curve fitting, see fitGrowth for available models
origin	logical (with default): logical value indicating if the growth curve should be forced to pass the origin
errMethod	character (with default): method used for equivalent dose error assessment. See function calED for details
nsim	integer (with default): desired number of randomly simulated equivalent dose obtained by Monte Carlo simulation
weight	logical (with default): logical value indicating if the growth curve should be fitted using a weighted procedure, see function fitGrowth for details
trial	logical (with default): logical value indicating if the growth curve should be fitted using other models if the given model fails, see function fitGrowth for details
nofit.rgd	integer (optional): regenerative doses that will not be used during the fitting. For example, if <code>nofit.rgd=6</code> then the sixth regenerative dose will not be used during growth curve fitting
Tn.above.3BG	logical (with default): logical value indicating if aliquot (grain) with Tn below 3 sigma BG should be rejected
TnBG.ratio.low	numeric (optional): lower limit on ratio of initial Tn signal to BG
rseTn.up	numeric (optional): upper limit on relative standard error of Tn in percent
FR.low	numeric (optional): lower limit on fast ratio of Tn

rcy1.range	vector (optional): a two-element vector indicating the lower and upper limits on recycling ratio 1, Example: rcy1.range=c(0.9,1.1)
rcy2.range	vector (optional): a two-element vector indicating the lower and upper limits on recycling ratio 2
rcy3.range	vector (optional): a two-element vector indicating the lower and upper limits on recycling ratio 3
rcp1.up	numeric (optional): upper limit on recuperation 1 (i.e., ratio of the sensitivity-corrected zero-dose signal to natural-dose signal) in percent
rcp2.up	numeric (optional): upper limit on recuperation 2 (i.e., ratio of the sensitivity-corrected zero-dose signal to maximum regenerative-dose signal) in percent
fom.up	numeric (optional): upper limit on figure of merit (FOM) values of growth curves in percent
rCs.up	numeric (optional): upper limit on reduced chi-square (RCS) values of growth curves
calED.method	character (optional): method used for equivalent dose calculation, i.e., "Interpolation" or "Extrapolation"
rseED.up	numeric (optional): upper limit on the relative standard error of equivalent dose in percent
use.se	logical (with default): logical value indicating if standard errors of values should be used during application of rejection criteria
outpdf	character (optional): if specified, results of SAR equivalent dose calculation will be written to a PDF file named "outpdf" and saved to the current work directory
outfile	character (optional): if specified, SAR equivalent doses related quantities will be written to a CSV file named "outfile" and saved to the current work directory

Value

Return an invisible **list** that contains the following elements:

LMpars	a list containing optimized parameters of growth curves of calculated (selected) SAR equivalent doses
Tn	values and standard errors of Tn of calculated (selected) SAR equivalent doses
Ltx	sensitivity-corrected natural-dose signals and associated standard errors used for SAR equivalent dose calculation
sarED	calculated (selected) SAR equivalent doses and associated standard errors
ConfInt	68 percent (one sigma) and 95 percent (two sigma) confidence intervals of SAR equivalent doses
agID	aliquot (grain) ID of calculated (selected) SAR equivalent doses
summary.info	a summary of the SAR equivalent dose calculation

Note

Rejection criteria used to select reliable SAR equivalent dose estimates can be categorized into three groups:

- (1) signal-related criteria, such as `Tn.above.3BG`, `TnBG.ratio.low`, `rseTn.up`, and `FR.low`;
- (2) growth-curve-related criteria, such as `rcy1.range`, `rcy2.range`, `rcy3.range`, `rcp1.up`, `rcp2.up`, `fom.up`, and `rcs.up`;
- (3) equivalent-dose-related criteria, such as `calED.method` and `rseED.up`.

References

Duller GAT, 2016. Analyst (v4.31.9), User Manual.

Murray AS, Wintle AG, 2000. Luminescence dating of quartz using improved single-aliquot regenerative-dose protocol. *Radiation Measurements*, 32(1): 57-73.

Wintle AG, Murray AS, 2006. A review of quartz optically stimulated luminescence characteristics and their relevance in single-aliquot regeneration dating protocols. *Radiation Measurements*, 41(4): 369-391.

See Also

[analyseBINdata](#); [fitGrowth](#); [calED](#); [calSGCED](#); [pickSARdata](#)

Examples

```
data(BIN)
obj_pickBIN <- pickBINdata(BIN, Position=c(2,4,6,8,10), Grain=0,
                          LType="OSL", view=FALSE)
obj_analyseBIN <- analyseBINdata(obj_pickBIN, nfchn=3, nlchn=20)
res_SARED <- calSARED(obj_analyseBIN, model="exp", origin=FALSE)
# plot(res_SARED$Tn[,1], res_SARED$sarED[,1], xlab="Tn", ylab="ED (<Gy>|<s>")
```

calSGCED

SGC Equivalent dose calculation and selection

Description

Calculating and selecting equivalent doses in a batch model according to the "standardised growth curve" (SGC) method suggested by Roberts and Duller (2004) or the "global standardised growth curve" (gSGC) method suggested by Li et al. (2015, 2016).

Usage

```
calSGCED(obj_analyseBIN, SGCpars, model, origin, avgDev,
          method = "SGC", SAR.Cycle = "N", errMethod = "sp",
          Tn.above.3BG = TRUE, TnBG.ratio.low = NULL,
          rseTn.up = NULL, FR.low = NULL, rseED.up = NULL,
          use.se = TRUE, outpdf = NULL, outfile = NULL)
```

Arguments

obj_analyseBIN	list(required) : an object of S3 class "analyseBIN" produced by function analyseBINdata or as_analyseBIN
SGCpars	vector(required) : optimized parameters of the SGC obtained using function lsNORM (or fitGrowth)
model	character(required) : fitting model used for obtaining SGCpars
origin	logical(required) : logical value indicating if established SGC passes the origin
avgDev	numeric(required) : average deviation (i.e., average fit error) of the SGC obtained using function fitGrowth or lsNORM . This quantity stands for the uncertainty of established SGC when assessing the equivalent dose error using the simple transformaion method
method	character(with default) : method used for equivalent dose calculation, i.e., method="SGC" (for the original SGC method) or method="gSGC" (for the improved SGC method)
SAR.Cycle	character(with default) : SAR cycles used for SGC equivalent dose calculation. Example: SAR.Cycle=c("N", "R3")
errMethod	character(with default) : method used for equivalent dose error assessment
Tn.above.3BG	logical(with default) : logical value indicating if aliquot (grain) with Tn below 3 sigma BG should be rejected
TnBG.ratio.low	numeric(optional) : lower limit on ratio of initial Tn signal to BG
rseTn.up	numeric(optional) : upper limit on relative standard error of Tn in percent
FR.low	numeric(optional) : lower limit on fast ratio of Tn
rseED.up	numeric(optional) : upper limit on the relative standard error of equivalent dose in percent
use.se	logical(with default) : logical value indicating if standard errors of values should be used during application of rejection criteria
outpdf	character(optional) : if specified, results of SGC equivalent dose calculation will be written to a PDF file named "outpdf" and saved to the current work directory
outfile	character(optional) : if specified, SGC equivalent doses related quantities will be written to a CSV file named "outfile" and saved to the current work directory

Value

Return an invisible [list](#) that contains the following elements:

scale.Ltx	scaled standardised natural-dose signals and associated standard errors used for SGC equivalent dose calculation. Note that standardised natural-dose signals will remain un-scaled if method="SGC"
sgcED	calculated SGC equivalent doses
ConfInt	68 percent (one sigma) and 95 percent (two sigma) confidence intervals of SGC equivalent doses
agID	aliquot (grain) ID of calculated (selected) SGC equivalent doses
summary.info	a summary of the SGC equivalent dose calculation

References

Li B, Roberts RG, Jacobs Z, Li SH, 2015. Potential of establishing a "global standardised growth curve" (gSGC) for optical dating of quartz from sediments. *Quaternary Geochronology*, 27: 94-104.

Li B, Jacobs Z, Roberts RG, 2016. Investigation of the applicability of standardised growth curves for OSL dating of quartz from Haa Fteah cave, Libya. *Quaternary Geochronology*, 35: 1-15.

Roberts HM, Duller GAT, 2004. Standardised growth curves for optical dating of sediment using multiple-grain aliquots. *Radiation Measurements*, 38(2): 241-252.

See Also

[fitGrowth](#); [lsNORM](#); [SARdata](#); [scaleSGCN](#); [calED](#); [calSARED](#)

Examples

```
data(SARdata)
### (1) gSGC ED calculation:
### gSGCpars were obtained using function "lsNORM".
gSGCpars <- c(137.440874251, 0.007997863, 2.462035263, -0.321536177)
avg.error2 <- 0.1111623
res <- calSGCED(as_analyseBIN(SARdata), gSGCpars, method="gSGC",
               model="gok", origin=FALSE, avgDev=avg.error2,
               SAR.Cycle=c("N","R3"))
print(res$sgcED)

### (2) SGC ED calculation (not run):
### SGCpars were obtained using function "fitGrowth".
# SGCpars <- c(183.474322547, 0.007038048, 4.254287622, -0.337734151)
# avg.error <- 0.3156259
# calSGCED(as_analyseBIN(SARdata), SGCpars, method="SGC", model="gok",
#          origin=FALSE, avgDev=avg.error, SAR.Cycle="N", outpdf="SGCED")

### (3) gSGC ED calculation and signal-related
### rejection criteria application (not run):
# data(BIN)
# res_pickBIN <- pickBINdata(BIN, LType="OSL")
# res_analyseBIN <- analyseBINdata(res_pickBIN, nfchn=4, nlchn=30)
# res_lsNORM <- lsNORM(res_analyseBIN$SARdata, model="gok", origin=FALSE)

# calSGCED(res_analyseBIN, SGCpars=res_lsNORM$LMpars2[,1],
#          model="gok", origin=FALSE, avgDev=res_lsNORM$avg.error2,
#          method="gSGC", SAR.Cycle=c("N","R3"), Tn.above.3BG=TRUE,
#          TnBG.ratio.low=4, rseTn.up=10, outpdf="foo", outfile="foo")
```

dbED

*De distribution summarization***Description**

Calculating statistical parameters (skewness, kurtosis, quantiles) for a number of equivalent dose values.

Usage

```
dbED(EDdata, plot = TRUE, typ = "pdf", from = NULL,
     to = NULL, step = NULL, nbin = 15, pcolor = "purple",
     psize = 1.5, outfile = NULL)
```

Arguments

EDdata	matrix(required) : a two-column matrix (i.e., equivalent dose values and associated standard errors)
plot	logical (with default): draw a plot or not
typ	character (with default): type of plot, typ="pdf" means a probability density plot and typ="hist" means a histogram plot
from	numeric (optional): desired lower limit on x-axis
to	numeric (optional): desired upper limit on x-axis
step	numeric (optional): a step-size used for constructing the probability density plot (if typ="pdf"). Smaller step value gives smoother density curve
nbin	integer (with default): desired number of intervals for the histogram (if typ="hist")
pcolor	character (with default): color of data points, input <code>colors()</code> to see available colors
psize	numeric (with default): size of data points
outfile	character (optional): if specified, calculated probability densities (if typ="pdf") will be written to a CSV file named "outfile" and saved to the current work directory

Value

Return a [list](#) that contains the following elements:

weight.ED	weighed mean of equivalent dose values and associated standard error
skewness	weighted skewness of equivalent dose values and associated standard error
kurtosis	kurtosis of equivalent dose values and associated standard error
quantile.ED	quantiles of equivalent dose values

References

Galbraith RF, 2010. On plotting OSL equivalent doses. *Ancient TL*, 28(1): 1-10.

Galbraith RF, Roberts RG, 2012. Statistical aspects of equivalent dose and error calculation and display in OSL dating: an overview and some recommendations. *Quaternary Geochronology*, 11: 1-27.

See Also

[psRadialPlot](#); [RadialPlotter](#); [EDdata](#)

Examples

```
data(EDdata)
dbED(EDdata$g111, typ="pdf")
```

decomp

OSL decay curve decomposition

Description

Decomposing a CW-OSL or LM-OSL decay curve to a given number of first-order exponential components using a combination of differential evolution and Levenberg-Marquardt algorithm suggested by Bluszcz and Adamiec (2006).

Usage

```
decomp(Sigdata, delay.off = c(0,0), ncomp = 2,
       constant = TRUE, typ = "cw", control.args = list(),
       weight = FALSE, plot = TRUE, log = "x", lwd = 2,
       curve.no = NULL, SAR.Cycle = NULL, irr.dose = NULL,
       outfile = NULL, transf = TRUE)
```

Arguments

Sigdata	matrix(required) : a two-column matrix (i.e., stimulation time and photon count values)
delay.off	vector (with default): a two-element vector indicating the "Delay" and "Off" values of the decay curves, i.e., <code>delay.off[1]=Delay, delay.off[2]=Off</code>
ncomp	integer (with default): number of decomposed components
constant	logical (with default): logical value indicating if a constant component should be subtracted from the decay curve
typ	character (with default): type of a decay curve (i.e., <code>typ="cw"</code> or <code>typ="lm"</code>)
control.args	list (with default): arguments used in the differential evolution algorithm, see details

weight	logical (with default): logical value indicating if the fit should be performed using a weighted procedure
plot	logical (with default): logical value indicating if the results should be plotted
log	character (with default): a character string which contains "x" if the x axis is to be logarithmic, "y" if the y axis is to be logarithmic and "xy" or "yx" if both axes are to be logarithmic
lwd	numeric (with default): width of curves (lines)
curve.no	numeric (optional): decay curve number
SAR.Cycle	numeric (optional): SAR cycle of the decay curve, Example: SAR.Cycle="R1"
irr.dose	numeric (optional): irradiation dose of the decay curve
outfile	character (optional): if specified, decomposed signal values will be written to a CSV file named "outfile" and saved to the current work directory
transf	logical (with default): do not use (for backward compatibility purpose)

Details

Function `decomp` decomposes an OSL decay curve to a specified number of components using a combination of differential evolution and Levenberg-Marquardt algorithm. Both CW-OSL and LM-OSL decay curves can be decomposed.

For a CW-OSL decay curve, the fitting model (Bluszcz and Adamiec, 2006) is:

$$I(t) = a_1 * b_1 * \exp(-b_1 * t) + \dots + a_k * b_k * \exp(-b_k * t),$$

where $k=1, 2, \dots, 7$, $I(t)$ is the luminescence intensity as a function of time, a is the number of trapped electrons, and b is the detrapping rate. The constant component is c if `constant=TRUE`.

For a LM-OSL decay curve, the fitting model (Bulur, 2000) is:

$$I(t) = a_1 * b_1 * (t/P) * \exp[-b_1 * t^2 / (2 * P)] + \dots + a_k * b_k * (t/P) * \exp[-b_k * t^2 / (2 * P)],$$

where $k=1, 2, \dots, 7$, and $I(t)$ is the luminescence intensity as a function of time, P is the total stimulation time, a is the number of trapped electrons, and b is the detrapping rate. The constant component is $c * (t/P)$ if `constant=TRUE`.

Parameters are initialized using a differential evolution method suggested by Bluszcz and Adamiec (2006), then the Levenberg-Marquardt algorithm (minpack: Fortran 90 version by John Burkardt, freely available at https://people.sc.fsu.edu/~jburkardt/f_src/minpack/minpack.html) will be performed to optimize the parameters. If `weight=TRUE`, the photon counts will be assumed to follow a Poisson distribution with a standard error equal to the square root of the number of photon counts, and the decay curve will be fitted using a weighted procedure. Setting `weight=TRUE` gives more weight to photon counts from slower decaying components.

Arguments in `control.args` that control the differential evolution algorithm include:

- (1) *factor*: the number of population members, $np = factor * ncomp$, default `factor=20`;
- (2) *f*: a weighting factor that lies between 0 and 1.2, default `f=0.5`;
- (3) *cr*: a crossover constant that lies between 0 and 1, default `cr=0.99`;
- (4) *maxiter*: maximum number of iterations, default `maxiter=500`;
- (5) *tol*: tolerance for stopping the iteration, the procedure will be terminated if all relative standard deviations of parameters are smaller than `tol`, default `tol=0.1`.

Value

Return an invisible [list](#) containing the following elements:

message	return 0 if fit succeeds, else 1
comp.sig	a matrix containing time, signal, and fitted signal values for each component
LMpars	optimized parameters for the decay curve
constant	estimated constant component, it returns 0 if constant=FALSE
value	minimized objective for the decay curve
FOM	figure of merit value for the decay curve in percent

Note

Arguments `curve.no`, `SAR.Cycle`, and `irr.dose` have nothing to do with decay curve fitting. They are used only for plotting purpose.

The model to be optimized should not be underdetermined. This means that the number of data points should exceed (or at least be equal to) the number of parameters. For a given model, this routine will return an error if any standard errors of parameters cannot be estimated by numerical difference-approximation. Function `decomp` in previous versions was bundled to function [decomp](#).

We would like to thank Professor Andrzej Bluszcz who helps us a lot during the programming of this function. Dr Jeong-Heon Choi is thanked for providing published data sets to test this routine.

References

Bluszcz A, 1996. Exponential function fitting to TL growth data and similar applications. *Geochronometria*, 13: 135-141.

Bluszcz A, Adamiec G, 2006. Application of differential evolution to fitting OSL decay curves. *Radiation Measurements*, 41(7-8): 886-891.

Bulur E, 2000. A simple transformation for converting CW-OSL curves to LM-OSL curves. *Radiation Measurements*, 32(2): 141-145.

Differential evolution algorithm, https://en.wikipedia.org/wiki/Differential_evolution

Jain M, Murray AS, Boetter-Jensen L, 2003. Characterisation of blue-light stimulated luminescence components in different quartz samples: implications for dose measurement. *Radiation Measurements*, 37(4-5): 441-449.

More JJ, 1978. "The Levenberg-Marquardt algorithm: implementation and theory," in *Lecture Notes in Mathematics: Numerical Analysis*, Springer-Verlag: Berlin. 105-116.

Further reading

Adamiec G, 2005. OSL decay curves-relationship between single- and multiple-grain aliquots. *Radiation Measurements*, 39(1): 63-75.

Balian HG, Eddy NW, 1977. Figure-of-merit (FOM), an improved criterion over the normalized chi-squared test for assessing goodness-of-fit of gamma-ray spectral peaks. *Nuclear Instruments and Methods*, 145(2): 389-95.

Choi JH, Duller GAT, Wintle AG, 2006. Analysis of quartz LM-OSL curves. *Ancient TL*, 24(1): 9-20.

Li SH, Li B, 2006. Dose measurement using the fast component of LM-OSL signals from quartz. *Radiation Measurements*, 41(5): 534-541.

Peng J, Dong ZB, Han FQ, Han YH, Dai XL, 2014. Estimating the number of components in an OSL decay curve using the Bayesian Information Criterion. *Geochronometria*, 41(4): 334-341.

See Also

[Signaldata](#); [pickBINdata](#); [fastED](#)

Examples

```
### Example 1:
data(Signaldata)
decomp(Signaldata$lm, ncomp=3, typ="lm",
       control.args=list(maxiter=10))

### Example 2 (not run):
# data(BIN)
# obj_pickBIN <- pickBINdata(BIN, Position=2, Run=2, view=TRUE,
#                             LType="OSL", force.matrix=TRUE)
# decomp(obj_pickBIN$BINdata[[1]], ncomp=2, log="xy")
```

EDdata

Equivalent dose values

Description

Two sets of equivalent dose values.

Usage

```
data(EDdata)
```

Format

A list that contains two sets of equivalent dose values:

gl11 35 equivalent dose values of a sand sample from the Tengger Desert (Peng and Han, 2013)

al3 84 equivalent dose values of an alluvial deposit from the andean precordillera (Schmidt et al., 2012)

References

Peng J, Han FQ, 2013. Selections of fast-component OSL signal using sediments from the south edge of Tengger Desert. *Acta Geoscientica Sinica*, 34(6): 757-762.

Schmidt S, Tsukamoto S, Salomon E, Frechen M, Hetzel R, 2012. Optical dating of alluvial deposits at the orogenic front of the andean precordillera (Mendoza, Argentina). *Geochronometria*, 39(1): 62-75.

See Also

[dbED](#); [psRadialPlot](#); [RadialPlotter](#); [mcFMM](#); [mcMAM](#); [optimSAM](#); [sensSAM](#)

Examples

```
# Not run.
# data(EDdata)
# names(EDdata)
```

fastED

Fast-component equivalent dose calculation

Description

Estimating a fast-, medium-, or slow-component equivalent dose using decay curves obtained from the single aliquot regenerative-dose (SAR) method.

Usage

```
fastED(Sigdata, Redose, delay.off = c(0,0), ncomp = 2,
       constant = TRUE, compIDX = 1, control.args = list(),
       typ = "cw", model = "gok", origin = FALSE, errMethod = "sp",
       nsim = 500, weight.decomp = FALSE, weight.fitGrowth = TRUE,
       trial = TRUE, nofit.rgd = NULL, outpdf = NULL, log = "x",
       lwd = 2, test.dose = NULL, agID = NULL)
```

Arguments

Sigdata	matrix(required) : a series of decay curves stored in a matrix column by column, the first column denotes stimulation time values, see details. Data structure of this kind can be obtained using function pickBINdata by setting argument <code>force.matrix=TRUE</code> , see examples
Redose	vector(required) : regenerative dose values. Example: <code>Redose=c(1,2,3,4,0,1)</code>
delay.off	vector(with default) : a two-element vector indicating the "Delay" and "Off" values of the decay curves, i.e., <code>delay.off[1]=Delay,delay.off[2]=Off</code>
ncomp	integer(with default) : number of components to be decomposed
constant	logical(with default) : logical value indicating if a constant background should be subtracted from the decay curve, see function decomp for details
compIDX	integer(with default) : index of the component to be extracted. For example, <code>compIDX=1</code> and <code>compIDX=2</code> indicate respectively that the fast- and medium-component signals will be used to calculate the equivalent dose. The index should not exceed the number of components to be decomposed
control.args	list(with default) : arguments used in the differential evolution algorithm, see function decomp for details

typ	character (with default): type of an OSL decay curve, only CW-OSL decay curve can be analyzed currently
model	character (with default): model used for growth curve fitting, see function fitGrowth for available models
origin	logical (with default): logical value indicating if the growth curve should be forced to pass the origin
errMethod	character (with default): method used for equivalent dose error assessment. See function calED for details
nsim	integer (with default): desired number of randomly simulated equivalent dose obtained by Monte Carlo simulation
weight.decomp	character (with default): logical value indicating if the decay curve should be fitted using a weighted procedure, see function decomp for details
weight.fitGrowth	character (with default): logical value indicating if the growth curve should be fitted using a weighted procedure, see function fitGrowth for details
trial	logical (with default): logical value indicating if the growth curve should be fitted using other models if the given model fails, see function fitGrowth for details
nofit.rgd	integer (optional): regenerative doses that will not be used during the fitting. For example, if <code>nofit.rgd=1</code> then the first regenerative dose will not be used during fast-, medium-, or slow-component growth curve fitting
outpdf	character (optional): if specified, results of fast-, medium-, or slow-component equivalent dose calculation will be written to a PDF file named "outpdf" and saved to the current work directory
log	character (with default): a character string which contains "x" if the x axis is to be logarithmic, "y" if the y axis is to be logarithmic and "xy" or "yx" if both axes are to be logarithmic
lwd	numeric (with default): width of curves (lines)
test.dose	numeric (optional): test dose of decay curves
agID	vector (optional): a three-element vector indicating aliquot (grain) ID, i.e., <code>agID[1]=NO</code> , <code>agID[2]=Position</code> , <code>agID[3]=Grain</code>

Details

Function [fastED](#) is used to estimate a fast-, medium-, or slow-component equivalent dose using data sets obtained from the SAR protocol (Murray and Wintle, 2000). The routine tries to decompose a series of decay curves to a specified number of components, then the numbers of trapped electrons from the fast-, medium-, or slow-component will be used to construct the growth curve to estimate a fast-, medium-, or slow-component equivalent dose. See function [decomp](#), [fitGrowth](#), and [calED](#) for more details concerning decay curve decomposition, growth curve fitting, and equivalent dose calculation, respectively.

Argument `Sigdata` is a column-matrix made up with stimulation time values and a number of decay curves:

Column.no	Description
I	Stimulation time values
II	Natural-dose signal values
III	Test-dose signal values for the natural-dose
IV	The 1th Regenerative-dose signal values
V	Test-dose signal values for the 1th regenerative-dose
VI	The 2th regenerative-dose signal values
VII	Test-dose signal values for the 2th regenerative-dose
...	...

Value

Return an invisible [list](#) containing the following elements:

decomp.pars	a list containing optimized parameters of successfully fitted decay curves
Curvedata	data sets used for building the fast-, medium-, or slow-component growth curve
Ltx	sensitivity-corrected natural-dose fast-, medium-, or slow-component signal and its standard error
LMpars	optimized parameters for the fast-, medium-, or slow-component growth curve
value	minimized objective for the fast-, medium-, or slow-component growth curve
avg.error	average fit error for the fast-, medium-, or slow-component growth curve
RCS	reduced chi-square value for the fast-, medium-, or slow-component growth curve
FOM	figure of merit value for the fast-, medium-, or slow-component growth curve in percent
calED.method	method used for calculating the fast-, medium-, or slow-component equivalent dose, i.e., "Interpolation" or "Extrapolation"
mcED	randomly simulated fast-, medium-, or slow-component equivalent doses
ED	fast-, medium-, or slow-component equivalent dose and its standard error
ConfInt	68 percent and 95 percent confidence interval of the fast-, medium-, or slow-component equivalent dose
RecyclingRatio1	the first fast-, medium-, or slow-component recycling ratio and its standard error
RecyclingRatio2	the second fast-, medium-, or slow-component recycling ratio and its standard error
RecyclingRatio3	the third fast-, medium-, or slow-component recycling ratio and its standard error
Recuperation1	the first fast-, medium-, or slow-component recuperation (i.e., ratio of the sensitivity-corrected zero-dose signal to natural-dose signal) and its standard error in percent
Recuperation2	the second fast-, medium-, or slow-component recuperation (i.e., ratio of the sensitivity-corrected zero-dose signal to the maximum regenerative-dose signal) and its standard error in percent

Note

Argument `test.dose` and `agID` have nothing to do with fast-, medium-, or slow-component equivalent dose calculation. They are used only for plotting purpose.

The number of trapped electrons that corresponds to the largest, the second largest, and the third largest decay rates will be regarded as the fast-, medium-, and slow-component signals, respectively, which cannot always ensure that pure fast-, medium-, or slow-component signals be extracted if an ultra-fast decaying component appears.

The authors thank Professor Sheng-Hua Li and Professor Geoff Duller for their helpful discussions concerning fast-component equivalent dose calculation.

References

Li SH, Li B, 2006. Dose measurement using the fast component of LM-OSL signals from quartz. *Radiation Measurements*, 41(5): 534-541.

Murray AS, Wintle AG, 2000. Luminescence dating of quartz using improved single-aliquot regenerative-dose protocol. *Radiation Measurements*, 32(1): 57-73.

See Also

[pickBINdata](#); [Signaldata](#); [fitGrowth](#); [decomp](#); [calED](#)

Examples

```
### Example 1 (not run):
# data(Signaldata)
# fastED(Signaldata$cw,Redose=c(80,160,240,320,0, 80)*0.13,
#       ncomp=3, constant=FALSE, compIDX=1, outpdf="fastED1")

# fastED(Signaldata$cw,Redose=c(80,160,240,320,0, 80)*0.13,
#       ncomp=3, constant=FALSE, compIDX=2, outpdf="mediumED1")

# fastED(Signaldata$cw,Redose=c(80,160,240,320,0, 80)*0.13,
#       ncomp=3, constant=FALSE, compIDX=3, outpdf="slowED1")

### Example 2 (not run):
# data(BIN)
# obj_pickBIN <- pickBINdata(BIN, Position=6, Grain=0,
#                             LType="OSL", force.matrix=TRUE)
# fastED(obj_pickBIN$BINdata[[1]], ncomp=2, constant=TRUE,
#       Redose=c(100,200,300,400,0,100)*0.13, outpdf="fastED2")
```

fitGrowth

*Growth curve fitting***Description**

Fitting growth curves using the Levenberg-Marquardt algorithm.

Usage

```
fitGrowth(Curvedata, model = "gok", origin = FALSE,
          weight = TRUE, trial = FALSE, plot = TRUE,
          nofit.rgd = NULL, agID = NULL, Tn = NULL,
          Tn3BG = NULL, TnBG.ratio = NULL, rseTn = NULL,
          FR = NULL, RecyclingRatio1 = NULL,
          RecyclingRatio2 = NULL, RecyclingRatio3 = NULL,
          Recuperation1 = NULL, Recuperation2 = NULL,
          LnTn.curve = NULL, TxTn = NULL)
```

Arguments

Curvedata	matrix(required) : a three-column matrix (i.e., regenerative doses, sensitivity-corrected regenerative-dose signals, and associated standard errors)
model	character (with default): model used for growth curve fitting, see details
origin	logical (optional): logical value indicating if the growth curve should be forced to pass the origin
weight	logical (with default): logical value indicating if the growth curve should be fitted using a weighted procedure, see details
trial	logical (with default): logical value indicating if the growth curve should be fitted using other models if the given model fails, see details
plot	logical (with default): logical value indicating if the results should be plotted
nofit.rgd	integer (optional): regenerative doses that will not be used during the fitting. For example, if <code>nofit.rgd=c(5,6)</code> then both the fifth and sixth regenerative doses will not be used during growth curve fitting
agID	vector (optional): a three-element vector indicating aliquot (grain) ID, i.e., <code>agID[1]=NO</code> , <code>agID[2]=Position</code> , <code>agID[3]=Grain</code>
Tn	vector (optional): a two-element vector containing value and standard error of Tn
Tn3BG	numeric (optional): 0-1 value indicating if Tn is more than 3 sigma above BG, 1 indicates <code>Tn>3_sigma_BG</code> , 0 indicates <code>Tn<=3_sigma_BG</code>
TnBG.ratio	vector (optional): a two-element vector containing value and standard error of ratio of initial Tn signal to BG
rseTn	numeric (optional): relative standard error of Tn in percent
FR	vector (optional): a two-element vector containing value and standard error of fast ratio of Tn

RecyclingRatio1	vector (optional): a two-element vector containing value and standard error of the first recycling ratio
RecyclingRatio2	vector (optional): a two-element vector containing value and standard error of the second recycling ratio
RecyclingRatio3	vector (optional): a two-element vector containing value and standard error of the third recycling ratio
Recuperation1	vector (optional): a two-element vector containing value and standard error of the first recuperation
Recuperation2	vector (optional): a two-element vector containing value and standard error of the second recuperation
LnTn.curve	list (optional): decay curve data for Ln and Tn, it should contain four elements, i.e., names(LnTn.curve)=c("Ln.x", "Ln.y", "Tn.x", "Tn.y")
TxTn	vector (optional): ratios of Tx to Tn for various SAR cycles

Details

In growth curve fitting using function `fitGrowth`, five models are available:

- (1) *"line"*: a linear model, $y=a*x+b$;
- (2) *"exp"*: a single saturation exponential model, $y=a*[1-\exp(-b*x)]+c$;
- (3) *"lexp"*: a single saturation exponential plus linear model, $y=a*[1-\exp(-b*x)]+c*x+d$;
- (4) *"dexp"*: a double saturation exponential model, $y=a*[1-\exp(-b*x)]+c*[1-\exp(-d*x)]+e$;
- (5) *"gok"*: a general order kinetic model (Guralnik et al., 2015), $y=a*[1-(1+b*c*x)^{-1/c}]+d$.

The fitting process is performed using the Levenberg-Marquardt algorithm (minpack: Fortran 90 source code by John Burkardt, freely available at https://people.sc.fsu.edu/~jburkardt/f_src/minpack/minpack.html). If `weight=TRUE`, a weighted procedure will be performed through weighting each data point by its inverse variance. User is advised to set argument `plot=TRUE` if possible to visualize the quality of fit.

Argument `trial=TRUE` means that if the growth curve can not be fitted successfully using the user-supplied model, then the procedure will try to fit other models instead:

Model	Tried model
"dexp"	c("dexp", "gok", "exp", "line")
"lexp"	c("lexp", "gok", "exp", "line")
"gok"	c("gok", "exp", "line")
"exp"	c("exp", "line")
"line"	c("line")

For example, if `model="dexp"` and `trial=TRUE`, then a number of models from sequence `c("dexp", "gok", "exp", "line")` will be applied one after another until the fit succeeds.

The required number of data points for each model is (value inside the parentheses denotes the required number of observations if the model passes the origin):

Model	Required NPoints
"dexp"	>=5 (>=4)
"lexp"	>=4 (>=3)
"gok"	>=4 (>=3)
"exp"	>=3 (>=2)
"line"	>=2 (>=1)

If user-provided data is not enough for model fitting (i.e., the number of data points is less than the number of parameters of a given model), then a model with less parameters will be fitted. For example, if 4 data points are fitted using a "dexp" (origin=FALSE) model that actually needs at least 5 data points, then a 4-parameter "gok" model will be fitted instead.

Value

Return a [list](#) that contains the following elements:

message	return 0 if the fit succeeds, else 1
fitIDX	Indices of dose points used in growth curve fitting
LMpars	optimized parameters for the growth curve
value	minimized objective for the growth curve
avg.error	average fit error for the growth curve
RCS	reduced chi-square value for the growth curve
FOM	figure of merit value for the growth curve in percent

Note

Arguments agID, Tn, Tn3BG, TnBG.ratio, rseTn, FR, RecyclingRatio1, RecyclingRatio2, RecyclingRatio3, Recuperation1, Recuperation2, LnTn.curve, TxTn have nothing to do with growth curve fitting. They are used only for plotting purpose.

The model to be optimized should not be underdetermined. This means that the number of data points should exceed (or at least be equal to) the number of parameters. For a given model, the procedure will return an error if any standard errors of parameters cannot be estimated by numerical difference-approximation.

References

- Balian HG, Eddy NW, 1977. Figure-of-merit (FOM), an improved criterion over the normalized chi-squared test for assessing goodness-of-fit of gamma-ray spectral peaks. *Nuclear Instruments and Methods*, 145(2): 389-95.
- Guralnik B, Li B, Jain M, Chen R, Paris RB, Murray AS, Li SH, Pagonis V, Valla PG, Herman F, 2015. Radiation-induced growth and isothermal decay of infrared-stimulated luminescence from feldspar. *Radiation Measurements*, 81: 224-231.
- More JJ, 1978. "The Levenberg-Marquardt algorithm: implementation and theory" in *Lecture Notes in Mathematics: Numerical Analysis*, Springer-Verlag: Berlin. 105-116.

See Also

[analyseBINdata](#); [SARdata](#); [calED](#); [calSARED](#); [fastED](#);
[pickSARdata](#); [lsNORM](#); [calSGCED](#)

Examples

```
### Example 1:
Curvedata <- cbind(c(0, 18, 36, 54, 72, 0, 18),
                  c(0.026, 1.55, 2.39, 3.46, 4.13, 0.023, 1.61),
                  c(0.005, 0.11, 0.27, 0.22, 0.20, 0.008, 0.24))
fitGrowth(Curvedata, model="gok", origin=FALSE, plot=TRUE)

### Example 2 (not run):
# data(SARdata)
# Curvedata <- SARdata[!is.element(SARdata[,2], "N"),3:5]
# fitGrowth(Curvedata, model="gok", origin=FALSE)
```

loadBINdata	<i>BIN file loading (importing)</i>
-------------	-------------------------------------

Description

Loading (importing) a BIN file into the R platform.

Usage

```
loadBINdata(filename, view = TRUE)
```

Arguments

filename **character(required)**: name(s) of file(s) (with file extension ".BIN", ".bin", "BINX", or "binx"), the file(s) must be available from the current working directory. Example: `filename=c("foo1.bin", "foo2.binx")`

view **logical(optional)**: logical value indicating if the loaded data should be visualized in a Summary Table

Details

Function `loadBINdata` is used for loading BIN (BINX) files into the R platform. Five versions of binary files (V3, V4, V6, V7, and V8) are loadable. It can load a single BIN (BINX) file or a number of files into R simultaneously.

Items reserved during the loading process include:

- (1) *Position*: Carousel position;
- (2) *Grain*: Grain number;
- (3) *Run*: Run number;
- (4) *Set*: Set number;

- (5) *DType*: Data type, includes: Natural, N+dose, bleach, Bleach+dose, Natural(Bleach), N+dose(Bleach), Dose, Background;
- (6) *IRRTime*: Irradiation time;
- (7) *NPoints*: number of data points;
- (8) *LType*: Luminescence type, includes: TL, OSL, IRSL, M-IR, M-VIS, TOL, TRPOS, RIR, RBR, USER, POSL, SGOSL, RL, XRF;
- (9) *Low*: Low (temperature, time, wavelength);
- (10) *High*: High (temperature, time, wavelength);
- (11) *Rate*: Rate (temperature, time, wavelength);
- (12) *Temperature*: Sample temperature;
- (13) *Delay*: TOL "delay" channels;
- (14) *On*: TOL "on" channels;
- (15) *Off*: TOL "off" channels;
- (16) *LightSource*: Light source, includes: None, Lamp, IRDiodes, CalibrationLED, BlueDiodes, WhiteLight, GreenLaser, IRLaser;
- (17) *AnTemp*: Annealing temperature;
- (18) *TimeSinceIrr*: Time since irradiation;
- (19) *Time*: Data collection time;
- (20) *Date*: Data collection date.

Value

Return an invisible [list](#) of S3 class object "loadBIN" containing the following elements:

records	a list containing loaded data records
tab	a table (data.frame) summarizing items of loaded data records

Note

We would like to appreciate Dr Lei Gao who prompts us to write this function and provides measured data sets to test this procedure.

References

Duller GAT, 2016. Analyst (v4.31.9), User Manual.

See Also

[pickBINdata](#); [analyseBINdata](#); [BIN](#)

Examples

```
### Not run.
### Ensure that file "foo.bin" is available
### from the current working directory.
# obj_loadBIN <- loadBINdata("foo.bin", view=TRUE)
# class(obj_loadBIN)
# obj_loadBIN$records
```

 lsNORM

Regenerative-dose signal optimization using the LS-normalisation procedure

Description

Optimizing standardised regenerative-dose signals according to the least-squares normalisation (LS-normalisation) procedure using an iterative scaling and fitting procedure proposed by Li et al. (2016).

Usage

```
lsNORM(SARdata, model = "gok", origin = FALSE,
       weight = FALSE, natural.rm = TRUE,
       norm.dose = NULL, maxiter = 10,
       plot = TRUE)
```

Arguments

SARdata	matrix(required) : SAR data used for performing the LS-normalisation procedure, it should contain five columns (i.e., NO, SAR.Cycle, Dose, Signal, and Signal.Err), see SARdata for details
model	character (with default): model used for growth curve fitting, see fitGrowth for available models
origin	logical (with default): logical value indicating if the growth curve should be forced to pass the origin
weight	logical (with default): logical value indicating if the growth curve should be fitted using a weighted procedure, see function fitGrowth for details
natural.rm	logical (with default): logical value indicating if the standardised natural-dose signal should be removed from SARdata
norm.dose	numeric (optional): regenerative-dose used for re-scaling established gSGC. For example, if norm.dose=100, then the signal value for a dose value of 100 (Gys) will be re-scaled to unity
maxiter	integer (with default): allowed maximum number of iterations during the LS-normalisation optimization process
plot	logical (with default): logical value indicating if the results should be plotted

Details

Function `lsNORM` is used for optimizing regenerative-dose signal data from a number of grains (aliquots) according to the least-squares normalisation (LS-normalisation) procedure outlined by Li et al. (2016) using an iterative scaling and fitting procedure.

The LS-normalisation procedure for growth curve optimization involves the following steps:

- (1) Fit standardised regenerative-dose signals from all of the aliquots;
- (2) Re-scale the individual growth curve from each aliquot using a scaling factor. The scaling factor for each aliquot is determined in a way such that the sum of squared residuals is minimized. Each aliquots is treated individually, and different scaling factors are calculated for different aliquots.
- (3) Iterate the fitting (step 1) and re-scaling (step 2). The iterative procedure is performed repeatedly until there is negligible change in the relative standard deviation of the normalised growth curve data.

Value

Return an invisible [list](#) that contains the following elements:

<code>norm.SARdata</code>	SAR data sets optimized using the LS-normalisation procedure
<code>sf</code>	scaling factor of standardised regenerative-dose signals
<code>iter</code>	number of iterations required
<code>LMpars1</code>	optimized parameters for the growth curve before LS-normalisation
<code>value1</code>	minimized objective for the growth curve before LS-normalisation
<code>avg.error1</code>	average fit error for the growth curve before LS-normalisation
<code>RCS1</code>	reduced chi-square value for the growth curve before LS-normalisation
<code>FOM1</code>	figure of merit value for the growth curve before LS-normalisation in percent
<code>LMpars2</code>	optimized parameters for the growth curve after LS-normalisation
<code>value2</code>	minimized objective for the growth curve after LS-normalisation
<code>avg.error2</code>	average fit error for the growth curve after LS-normalisation
<code>RCS2</code>	reduced chi-square value for the growth curve after LS-normalisation
<code>FOM2</code>	figure of merit value for the growth curve after LS-normalisation in percent

References

Li B, Jacobs Z, Roberts RG, 2016. Investigation of the applicability of standardised growth curves for OSL dating of quartz from Haua Fteah cave, Libya. *Quaternary Geochronology*, 35: 1-15.

See Also

[analyseBINdata](#); [fitGrowth](#); [SARdata](#); [scaleSGCN](#); [calSGCED](#)

Examples

```
### Example 1:
data(SARdata)
# Use only the first five aliquots of SARdata.
Data <- SARdata[1:40,]
res_lsNORM <- lsNORM(Data, model="gok")
res_lsNORM$norm.SARdata

### Example 2 (not run):
# data(BIN)
# obj_pickBIN <- pickBINdata(BIN, Position=1:48, Grain=0,
#                             LType="OSL", view=FALSE)
# obj_analyseBIN <- analyseBINdata(obj_pickBIN, nfchn=3, nlchn=20)
# lsNORM(obj_analyseBIN$SARdata, norm.dose=300)
```

 mcFMM

Finite mixture age model optimization (using a Markov chain Monte Carlo method)

Description

Sampling from the joint-likelihood functions of finite mixture age models (include the central age model) using a Markov chain Monte Carlo (MCMC) method.

Usage

```
mcCAM(EDdata, addsigma = 0, iflog = TRUE,
      nsim = 50000, inis = list(), control.args = list())

mcFMM(EDdata, ncomp = 2, addsigma = 0, iflog = TRUE,
      nsim = 50000, inis = list(), control.args = list())
```

Arguments

EDdata	matrix(required) : a two-column matrix (i.e., equivalent dose values and associated standard errors)
ncomp	integer (with default): number of components
addsigma	numeric (with default): additional uncertainty, i.e., the sigma _b value
iflog	logical (with default): transform equivalent dose values to log-scale or not
nsim	integer (with default): desired number of iterations
inis	list (with default): initial state of parameters. Example: <code>inis=list(p1=1,p2=1,mu1=5,mu2=10)</code> in FMM2 (the sum of p1 and p2 will be normalized to 1 during the simulation)
control.args	list (with default): arguments used in the Slice Sampling algorithm, see details

Details

Function `mcFMM` is used for sampling from the joint-likelihood functions of finite mixture age models (include the central age model) using a Markov chain Monte Carlo sampling algorithm called Slice Sampling (Neal, 2003). Three arguments (`control.args`) are used for controlling the sampling process:

- (1) `w`: size of the steps for creating an interval from which to sample, default `w=1`;
- (2) `m`: limit on steps for expanding an interval, `m<=1` means no limit on the expansion, `m>1` means the interval is expanded with a finite number of iterations, default `m=-100`;
- (3) `nstart`: maximum number of trials for updating a variable in an iteration. It can be used for monitoring the stability of the simulation. For example, a MAM4 is likely to crash down for data sets with small numbers of data points or less dispersed distributions (see section 8.3 of Galbraith and Roberts, 2012 for a discussion), and sometimes more than one trial (i.e., using `nstart>1`) is required to complete the sampling process, default `nstart=1`.

Value

Return an invisible `list` of S3 class object "mcAgeModels" including the following elements:

<code>EDdata</code>	equivalent dose values
<code>addsigma</code>	additional uncertainty
<code>model</code>	fitting model
<code>iflog</code>	transform equivalent dose values to log-scale or not
<code>nsim</code>	number of iterations
<code>chains</code>	simulated samples of parameters

References

Galbraith RF, Green P, 1990. Estimating the component ages in a finite mixture. International Journal of Radiation Applications and Instrumentation. Part D. Nuclear Tracks and Radiation Measurements, 17: 197-206.

Neal RM, 2003. "Slice sampling" (with discussion). Annals of Statistics, 31(3): 705-767. Software is freely available at <https://glizen.com/radfordneal/slice.software.html>.

Peng J, Dong ZB, Han FQ, 2016. Application of slice sampling method for optimizing OSL age models used for equivalent dose determination. Progress in Geography, 35(1): 78-88. (In Chinese).

See Also

[mcMAM](#); [reportMC](#); [RadialPlotter](#); [optimSAM](#); [sensSAM](#); [EDdata](#)

Examples

```
# Not run.
# data(EDdata)
# Construct a MCMC chain for CAM.
# obj<-mcCAM(EDdata$gl11,nsim=5000)
# reportMC(obj,thin=2,burn=1e3)
```



```
# Construct a MCMC chain for FMM3.
# obj<-mcFMM(EDdata$gl11,ncomp=3,nsim=5000)
# reportMC(obj,thin=2,burn=1e3)
```

mcMAM	<i>Optimization of the minimum (maximum) age model (using a Markov chain Monte Carlo method)</i>
-------	--

Description

Sampling from the joint-likelihood function of the minimum (maximum) age model using a Markov chain Monte Carlo (MCMC) method.

Usage

```
mcMAM(EDdata, ncomp = -1, addsigma = 0, iflog = TRUE,
      nsim = 50000, inis = list(), control.args = list())
```

Arguments

EDdata	matrix(required) : a two-column matrix (i.e., equivalent dose values and associated standard errors)
ncomp	integer (with default): number of components, ncomp=-1, ncomp=-2, ncomp=-3, or ncomp=-4 indicate fitting the "MAM3", "MAM4", "MXAM3", and "MXAM4", respectively
addsigma	numeric (with default): additional uncertainty, i.e., the sigmab value
iflog	logical (with default): transform equivalent dose values to log-scale or not
nsim	integer (with default): desired number of iterations
inis	list (with default): initial state of parameters. Example: inis=list(p=0.1,gamma=20,sigma=0.3) when ncomp=-1
control.args	list (with default): arguments used by the Slice Sampling algorithm, see function mcFMM for details

Value

Return an invisible [list](#) of S3 class object "mcAgeModels". See [mcFMM](#) for details.

References

- Galbraith RF, Roberts RG, Laslett GM, Yoshida H, Olley JM, 1999. Optical dating of single grains of quartz from Jinmium rock shelter, northern Australia. Part I: experimental design and statistical models. *Archaeometry*, 41(2): 339-364.
- Neal RM, 2003. "Slice sampling" (with discussion). *Annals of Statistics*, 31(3): 705-767. Software is freely available at <https://glizen.com/radfordneal/slice.software.html>.
- Peng J, Dong ZB, Han FQ, 2016. Application of slice sampling method for optimizing OSL age models used for equivalent dose determination. *Progress in Geography*, 35(1): 78-88. (In Chinese).

See Also

[mcFMM](#); [reportMC](#); [RadialPlotter](#); [EDdata](#); [optimSAM](#); [sensSAM](#)

Examples

```
# Not run.
# data(EDdata)
# Construct a MCMC chain for MAM3.
# obj<-mcMAM(EDdata$a13,ncomp=-1,addsigma=0.1,nsim=5000)
# reportMC(obj,burn=1e3,thin=2)
#
# The convergence of the simulations may be diagnosed with
# the Gelman and Rubin's convergence diagnostic.
# library(coda) # Only if package "coda" has been installed.
# args<-list(nstart=50)
# inis1<-list(p=0.01,gamma=26,mu=104,sigma=0.01)
# inis2<-list(p=0.99,gamma=100,mu=104,sigma=4.99)
# obj1<-mcMAM(EDdata$a13,ncomp=-2,nsim=3000,inis=inis1,control.args=args)
# obj2<-mcMAM(EDdata$a13,ncomp=-2,nsim=3000,inis=inis2,control.args=args)
# chain1<-mcmc(obj1$chains)
# chain2<-mcmc(obj2$chains)
# chains<-mcmc.list(chain1,chain2)
# gelman.plot(chains)
```

optimSAM

Optimization of statistical age models

Description

Estimating the parameters of statistical age models, including the common age model (COM), the central age model (CAM), the minimum age model (MAM), the maximum age model (MXAM), and the finite mixture age model (FMM), using the Maximum Likelihood Estimation method.

Usage

```
optimSAM(EDdata, model = "cam", addsigma = 0, iflog = TRUE, maxcomp = 6)
```

Arguments

EDdata	matrix(required) : a two-column matrix (i.e., equivalent dose values and associated standard errors)
model	character (with default): the fitting model, one of "com", "cam", "mam3", "mam4", "mxam3", "mxam4", "fmm0", "fmm1", "fmm2", ..., "fmm9"
addsigma	numeric (with default): additional uncertainty, i.e., the sigmab value
iflog	logical (with default): transform equivalent dose values to log-scale or not
maxcomp	integer (with default): the maximum number of components in FMM

Value

Return a [list](#) that contains the following elements:

<code>pars</code>	optimized parameters, the name of the parameter of COM is "COM.De", that of CAM are c("CAM.OD", "CAM.De"), that of MAM3 are c("Prop", "MAM3.De", "Sigma"), that of MXAM3 are c("Prop", "MXAM3.De", "Sigma"), that of MAM4 are c("Prop", "MAM4.De", "Mu", "Sigma"), that of MXAM4 are c("Prop", "MXAM4.De", "Mu", "Sigma"), and that of FMM are c("Prop", "FMM.De")
<code>maxlik</code>	optimized maximum logged likelihood value
<code>bic</code>	calculated Bayesian Information Criterion (BIC) value

References

- Galbraith RF, 1988. Graphical display of estimates having differing standard errors. *Technometrics*, 30(3): 271-281.
- Galbraith RF, 1990. The radial plot: Graphical assessment of spread in ages. *International Journal of Radiation Applications and Instrumentation. Part D. Nuclear Tracks and Radiation Measurements*, 17(3): 207-214.
- Galbraith RF, Green P, 1990. Estimating the component ages in a finite mixture. *International Journal of Radiation Applications and Instrumentation. Part D. Nuclear Tracks and Radiation Measurements*, 17: 197-206.
- Galbraith RF, Laslett GM, 1993. Statistical models for mixed fission track ages. *Nuclear Tracks And Radiation Measurements*, 21(4): 459-470.
- Galbraith RF, 1994. Some applications of radial plots. *Journal of the American Statistical Association*, 89(428): 1232-1242.
- Galbraith RF, Roberts RG, Laslett GM, Yoshida H, Olley JM, 1999. Optical dating of single grains of quartz from Jinnium rock shelter, northern Australia. Part I: experimental design and statistical models. *Archaeometry*, 41(2): 339-364.
- Galbraith RF, 2005. *Statistics for fission track analysis*. Chapman & Hall/CRC Press.
- Galbraith RF, 2010. On plotting OSL equivalent doses. *Ancient TL*, 28(1): 1-10.
- Galbraith RF, Roberts RG, 2012. Statistical aspects of equivalent dose and error calculation and display in OSL dating: an overview and some recommendations. *Quaternary Geochronology*, 11: 1-27.

See Also

[mcMAM](#); [mcFMM](#); [dbED](#); [psRadialPlot](#); [RadialPlotter](#); [EDdata](#)

Examples

```
data(EDdata)

### Fitting a 3-component FMM.
optimSAM(EDdata$al3, model="fmm3", addsigma=0)

### Fitting a 4-parameter MXAM.
optimSAM(EDdata$al3, model="mxam4", addsigma=0.1)
```

pickBINdata

*BIN data set selection***Description**

Extracting data sets from a loaded BIN (BINX) file.

Usage

```
pickBINdata(obj_loadBIN, Position = NULL, Grain = NULL,
            Run = NULL, Set = NULL, DType = NULL,
            IRRTime = NULL, NPoints = NULL, LType = NULL,
            Low = NULL, High = NULL, Rate = NULL,
            Temperature = NULL, Delay = NULL, On = NULL,
            Off = NULL, LightSource = NULL, AnTemp = NULL,
            TimeSinceIrr = NULL, view = TRUE,
            manual.select = FALSE, force.matrix = FALSE)
```

Arguments

obj_loadBIN	list(required) : an object of S3 class "loadBIN" produced by function <code>loadBINdata</code>
Position	vector(optional) : carousel position, Example: Position=1:48
Grain	vector(optional) : grain number
Run	vector(optional) : run number
Set	vector(optional) : set number
DType	character(optional) : a character vector indicating data type, Example: DType=c("Natural", "N+dose")
IRRTime	vector(optional) : irradiation time
NPoints	vector(optional) : number of data points
LType	character(optional) : a character vector indicating luminescence types, Example: LType="OSL"
Low	vector(optional) : lower limit on temperature, time, or wavelength
High	vector(optional) : upper limit on temperature, time, or wavelength
Rate	vector(optional) : increasing rate of temperature, time, or wavelength
Temperature	vector(optional) : a vector indicating the sample temperatures
Delay	vector(optional) : TOL "delay" channels
On	vector(optional) : TOL "on" channels
Off	vector(optional) : TOL "off" channels
LightSource	character(optional) : a character vector indicating light source, Example: LightSource="BlueDiodes"
AnTemp	vector(optional) : annealing temperature

TimeSinceIrr	vector (optional): time since irradiation
view	logical (with default): logical value indicating if the loaded data should be visualized in a Summary Table
manual.select	logical (with default): logical value indicating if the loaded data should be selected manually using a Summary Table
force.matrix	logical (with default): logical value indicating if the picked data sets of an aliquot (grain) should be transformed into a matrix

Details

Function `pickBINdata` is used for pick up data sets from an object of S3 class "loadBIN" generated using function `loadBINdata`. Set `force.matrix=TRUE` will transform data sets of an aliquot (grain) into a matrix, the transformation fails if data sets have different x (temperature, time, or wavelength) coordinates. Transformed data sets stored in a matrix can be visualize via `matplot` (see examples).

Value

Return an invisible **list** of S3 class object "pickBIN" containing two elements:

BINdata	selected BIN data
agID	Aliquot or grain ID (i.e., <code>c("NO", "Position", "Grain")</code>) of selected data sets, it returns NULL if <code>force.matrix=TRUE</code>

References

Duller GAT, 2016. Analyst (v4.31.9), User Manual.

See Also

[loadBINdata](#); [analyseBINdata](#); [BIN](#); [decomp](#); [fastED](#)

Examples

```
### Example 1 (visualize decay curves for Position=2):
data(BIN)
obj_pickBIN <- pickBINdata(BIN, Position=2, view=FALSE,
                           LType="OSL", force.matrix=TRUE)
matplot(obj_pickBIN$BINdata[[1]][,1],
        obj_pickBIN$BINdata[[1]][,-1],
        main="Decay curves",
        xlab="Stimulation time (s)",
        ylab="Photon counts",
        type="l", log="xy")

### Example 2 (visualize test-dose decay curves for Position=2):
obj_pickBIN <- pickBINdata(BIN, Position=2, Run=c(5,11,17,23,29,34,40),
                           view=FALSE, LType="OSL", force.matrix=TRUE)
matplot(obj_pickBIN$BINdata[[1]][,1],
        obj_pickBIN$BINdata[[1]][,-1],
        main="Test-dose decay curves",
```

```

xlab="Stimulation time (s)",
ylab="Photon counts",
type="l", log="xy")

### Example 3 (visualize regenerative-dose decay curves for Position=2):
obj_pickBIN <- pickBINdata(BIN, Position=2, Run=c(8,14,20,26,31,37),
                          view=FALSE, LType="OSL", force.matrix=TRUE)
matplot(obj_pickBIN$BINdata[[1]][,1],
        obj_pickBIN$BINdata[[1]][,-1],
        main="Regenerative-dose decay curves",
        xlab="Stimulation time (s)",
        ylab="Photon counts",
        type="l", log="xy")

```

pickSARdata

SAR data set selection

Description

Selecting SAR data sets (growth curves) in a batch model according to specified rejection criteria.

Usage

```

pickSARdata(obj_analyseBIN, model = "gok", origin = FALSE,
            weight = TRUE, trial = TRUE, nofit.rgd = NULL,
            Tn.above.3BG = TRUE, TnBG.ratio.low = NULL,
            rseTn.up = NULL, FR.low = NULL, rcy1.range = NULL,
            rcy2.range = NULL, rcy3.range = NULL,
            rcp1.up = NULL, rcp2.up = NULL, fom.up = NULL,
            rcs.up = NULL, use.se = TRUE, norm.dose = NULL,
            outpdf = NULL, outfile = NULL)

```

Arguments

`obj_analyseBIN` **list(required)**: an object of S3 class "analyseBIN" produced by function [analyseBINdata](#) or [as_analyseBIN](#)

`model` **character**(with default): model used for growth curve fitting, see [fitGrowth](#) for available models

`origin` **logical**(with default): logical value indicating if the growth curve should be forced to pass the origin

`weight` **logical**(with default): logical value indicating if the growth curve should be fitted using a weighted procedure, see function [fitGrowth](#) for details

`trial` **logical**(with default): logical value indicating if the growth curve should be fitted using other models if the given model fails, see function [fitGrowth](#) for details

`nofit.rgd` **integer**(optional): regenerative doses that will not be used during the fitting. For example, if `nofit.rgd=2` then the second regenerative dose will not be used during growth curve fitting

Tn.above.3BG	logical (with default): logical value indicating if aliquot (grain) with Tn below 3 sigma BG should be rejected
TnBG.ratio.low	numeric (optional): lower limit on ratio of initial Tn signal to BG
rseTn.up	numeric (optional): upper limit on relative standard error of Tn in percent
FR.low	numeric (optional): lower limit on fast ratio of Tn
rcy1.range	vector (optional): a two-element vector indicating the lower and upper limits on recycling ratio 1, Example: rcy1.range=c(0.9, 1.1)
rcy2.range	vector (optional): a two-element vector indicating the lower and upper limits on recycling ratio 2
rcy3.range	vector (optional): a two-element vector indicating the lower and upper limits on recycling ratio 3
rcp1.up	numeric (optional): upper limit on recuperation 1 (i.e., ratio of the sensitivity-corrected zero-dose signal to natural-dose signal) in percent
rcp2.up	numeric (optional): upper limit on recuperation 2 (i.e., ratio of the sensitivity-corrected zero-dose signal to maximum regenerative-dose signal) in percent
fom.up	numeric (optional): upper limit on figure of merit (FOM) values of growth curves in percent
rCS.up	numeric (optional): upper limit on reduced chi-square (RCS) values of growth curves
use.se	logical (with default): logical value indicating if standard errors of values should be used during application of rejection criteria
norm.dose	numeric (optional): dose value used for SAR data set re-normalisation, for example, if norm.dose=100, then sensitivity-corrected signal for Redose=100 obtained through growth curve fitting will be used to re-normalise a SAR data set
outpdf	character (optional): if specified, results of growth curve fitting will be written to a PDF file named "outpdf" and saved to the current work directory
outfile	character (optional): if specified, SAR data related quantities will be written to a CSV file named "outfile" and saved to the current work directory

Value

Return an invisible **list** that contains the following elements:

LMpars	a list containing optimized parameters of growth curves of selected SAR data sets
SARdata	a data.frame containing selected SAR data sets
norm.SARdata	a data.frame containing re-normalised SAR data sets, it returns NULL if norm.dose=NULL
agID	aliquot or grain ID (i.e., c("N0", "Position", "Grain")) of selected SAR data
summary.info	a summary of the SAR data selection

See Also

[analyseBINdata](#); [fitGrowth](#); [lsNORM](#); [calSARED](#)

Examples

```
# Not run.
# data(BIN)
# obj_pickBIN <- pickBINdata(BIN, Position=1:48, Grain=0,
#                             LType="OSL", view=FALSE)
# obj_analyseBIN <- analyseBINdata(obj_pickBIN, nfchn=3, nlchn=20)
# pickSARdata(obj_analyseBIN, model="gok", fom.up=3, outpdf="SARdata")
```

psRadialPlot

Pseudo radial plot drawing

Description

Drawing a pseudo (simplified) radial plot.

Usage

```
psRadialPlot(EDdata, addsigma = 0, dose = NULL,
             zmin = NULL, zmax = NULL, ntick = 6,
             digits = 2, pcolor = "blue", psize = 1,
             rg = 2, zlabel = "De (Gy)")
```

Arguments

EDdata	matrix(required) : a two-column matrix (i.e., equivalent dose values and associated standard errors)
addsigma	numeric (with default): additional uncertainty
dose	vector (optional): dose population(s) to be drawn
zmin	numeric (with default): lower limit on z-axis
zmax	numeric (with default): upper limit on z-axis
ntick	integer (with default): desired number of ticks in z-axis
digits	integer (with default): number of decimal places or significant digits for values shown in z-axis
pcolor	character (with default): color of a data point, input <code>colors()</code> to see more available colors
psize	numeric (with default): size of a data point
rg	integer (with default): range of a dose population, 0=dose, 1=dose+/-sigma, 2=dose+/-2sigma
zlabel	character (with default): title for the z-axis

Details

Function `psRadialPlot` is used for drawing a simplified radial plot in which the z-axis is a straight line. The pseudo radial plot is easier to construct compared to the regular radial plot. This function can be adopted to display estimates that have different error estimates in any field of the analytical sciences. Note that the function handles datasets in log-scale, so any minus observation is not allowed.

Value

Return a pseudo radial plot

References

Galbraith RF, 1988. Graphical display of estimates having differing standard errors. *Technometrics*, 30(3): 271-281.

Galbraith RF, 1994. Some applications of radial plots. *Journal of the American Statistical Association*, 89(428): 1232-1242.

Galbraith RF, 2010. On plotting OSL equivalent doses. *Ancient TL*, 28(1): 1-10.

Galbraith RF, Roberts RG, Laslett GM, Yoshida H, Olley JM, 1999. Optical dating of single grains of quartz from Jinnium rock shelter, northern Australia. Part I: experimental design and statistical models. *Archaeometry*, 41(2): 339-364.

See Also

[dbED](#); [RadialPlotter](#); [EDdata](#)

Examples

```
data(EDdata)
psRadialPlot(EDdata$a13, addsigma=0.10,
             dose=c(39.14, 51.27, 79.14), digits=1,
             zmin=30, zmax=100, ntick=10, rg=1)
```

RadialPlotter	<i>Statistical age model optimization (with a Maximum Likelihood Estimation method)</i>
---------------	---

Description

Depending on the specified number of components, this function performs statistical age models analysis reviewed in Galbraith and Roberts (2012) dynamically using a Maximum Likelihood Estimation method. Age models that can be applied include: central age model (CAM), minimum age model (MAM), and finite mixture age model (FMM).

Usage

```
RadialPlotter(EDdata, ncomp = 0, addsigma = 0,
             maxcomp = 6, algorithm = c("port", "lbfgsb"),
             plot = TRUE, pcolor = "blue", psize = 1.5,
             kratio = 0.3, zscale = NULL)
```

Arguments

EDdata	matrix(required) : a two-column matrix (i.e., equivalent dose values and associated standard errors)
ncomp	integer (with default): number of components, ncomp=-1, ncomp=-2, and ncomp=1 mean respectively fitting "MAM3", "MAM4", and "CAM", ncomp=0 means fitting "FMM" with an automatically optimized number of components, and ncomp=k (k>=2) means fitting "FMM" with k components
addsigma	numeric (with default): additional uncertainty, i.e., the sigmab value
maxcomp	integer (with default): maximum number of components in FMM
algorithm	character (with default): algorithm used for optimizing MAM, default algorithm="port"
plot	logical (with default): draw a radial plot or not
pcolor	character (with default): color of a data point, input <code>colors()</code> to see more available colors
psize	numeric (with default): size of a data point
kratio	numeric (with default): argument controlling the shape of zscale
zscale	vector (optional): argument controlling the scale of z-axis. Example: <code>zscale=seq(min(EDdata),max(EDdata),by=3L)</code>

Details

Both CAM and FMM are fitted using a iterative Maximum Likelihood Estimation procedure outlined by Galbraith (1988), while MAM can be estimated using either the "L-BFGS-B" algorithm (**R** function `optim` in package *stats*) or the "port" algorithm (**R** function `nlminb` in package *stats*).

Value

Return an object of S3 class "RadialPlotter" that contains the following elements:

pars	optimized parameters, the names of CAM parameters are <code>c("CAM.Od", "CAM.De")</code> , those of MAM3 paramters are <code>c("Prop", "MAM3.De", "Sigma")</code> , those of MAM4 parameters are <code>c("Prop", "MAM4.De", "Mu", "Sigma")</code> , and those of FMM parameters are <code>c("Prop", "FMM.De")</code>
maxlik	optimized maximum logged likelihood value
bic	calculated Bayesian Information Criterion (BIC) value

Note

Function `RadialPlotter` was given the same name as the *Java* package *RadialPlotter* written by Pieter Vermeesch (Vermeesch, 2009). Note that this function fits a model in log-scale, hence any minus equivalent dose value is not allowed, and that the procedure will return an error if any standard error of a parameter cannot be estimated by numerical difference-approximation.

The original **S** code for drawing a radial plot was written by Rex Galbraith and was transformed to **R** by Sebastian Kreuzer. The code for drawing radial plot in this function was modified from package

Luminescence written by Kreuzer et al. (2012). We thank Dr Rex Galbraith for his permission to modify and bundle the code to this function. We also thank Dr Silke Schmidt, Dr Helena Rodnight, Dr Xian-Jiao Ou, and Dr Amanda Keen-Zebert for providing published OSL data sets to test this routine.

This function only considered the optimization of statistical age models (including CAM, MAM, and FMM) in a log-scale and will not be updated in future. The newly developed function **optimSAM** allows the optimization of age models (including COM, MAM, MXAM, and FMM) in either log- or unlog-scale, and the accompanied function **sensSAM** allows the optimization of these age models with a number of different sizes of additional uncertainty (sigmab).

References

- Galbraith RF, 1988. Graphical display of estimates having differing standard errors. *Technometrics*, 30(3): 271-281.
- Galbraith RF, 1990. The radial plot: Graphical assessment of spread in ages. *International Journal of Radiation Applications and Instrumentation. Part D. Nuclear Tracks and Radiation Measurements*, 17(3): 207-214.
- Galbraith RF, Green P, 1990. Estimating the component ages in a finite mixture. *International Journal of Radiation Applications and Instrumentation. Part D. Nuclear Tracks and Radiation Measurements*, 17: 197-206.
- Galbraith RF, Laslett GM, 1993. Statistical models for mixed fission track ages. *Nuclear Tracks And Radiation Measurements*, 21(4): 459-470.
- Galbraith RF, 1994. Some applications of radial plots. *Journal of the American Statistical Association*, 89(428): 1232-1242.
- Galbraith RF, Roberts RG, Laslett GM, Yoshida H, Olley JM, 1999. Optical dating of single grains of quartz from Jinmium rock shelter, northern Australia. Part I: experimental design and statistical models. *Archaeometry*, 41(2): 339-364.
- Galbraith RF, 2005. *Statistics for fission track analysis*. Chapman & Hall/CRC Press.
- Galbraith RF, 2010. On plotting OSL equivalent doses. *Ancient TL*, 28(1): 1-10.
- Galbraith RF, Roberts RG, 2012. Statistical aspects of equivalent dose and error calculation and display in OSL dating: an overview and some recommendations. *Quaternary Geochronology*, 11: 1-27.

Further reading

- Duller GAT, 2008. Single-grain optical dating of Quaternary sediments: why aliquot size matters in luminescence dating. *Boreas*, 37(4): 589-612.
- Kreuzer S, Schmidt C, Fuchs MC, Dietze M, Fischer M, Fuchs M, 2012. Introducing an R package for luminescence dating analysis. *Ancient TL*, 30(1): 1-8. Software is freely available at <https://CRAN.R-project.org/package=Luminescence>.
- Rodnight H, 2008. How many equivalent dose values are needed to obtain a reproducible distribution? *Ancient TL*, 26(1): 3-10.
- Rodnight H, Duller GAT, Wintle AG, Tooth S, 2006. Assessing the reproducibility and accuracy of optical dating of fluvial deposits. *Quaternary Geochronology*, 1(2): 109-120.

Schmidt S, Tsukamoto S, Salomon E, Frechen M, Hetzel R, 2012. Optical dating of alluvial deposits at the orogenic front of the andean precordillera (Mendoza, Argentina). *Geochronometria*, 39(1): 62-75.

Vermeesch P, 2009. RadialPlotter: a Java application for fission track, luminescence and other radial plots. *Radiation Measurements*, 44: 409-410. Software is freely available at <https://www.ucl.ac.uk/~ucfbpve/radialplotter/>.

Peng J, Li B, Jacobs Z, 2020. Modelling heterogeneously bleached single-grain equivalent dose distributions: Implications for the reliability of burial dose determination. *Quaternary Geochronology*, 60: 101108.

Peng J, Li B, Jacobs Z, Gliganic LA, 2023. Optical dating of sediments affected by post-depositional mixing: Modelling, synthesizing and implications. *Catena*, 232: 107383.

See Also

[mcMAM](#); [mcFMM](#); [dbED](#); [psRadialPlot](#); [EDdata](#); [optimSAM](#); [sensSAM](#)

Examples

```
data(EDdata)
# Find out the appropriate number of components
# in FMM and fit automatically.
RadialPlotter(EDdata$a13,zscale=seq(24,93,7))

# Fit MAM3 (not run).
# RadialPlotter(EDdata$g111,ncomp=-1,zscale=seq(20,37,3))
```

reportMC

Reporting MCMC outputs for statistical age models

Description

Summarizing distributions of parameters simulated from statistical age models using a Markov Chain Monte Carlo method.

Usage

```
reportMC(obj, burn = 10000, thin = 5,
         plot = TRUE, outfile = NULL, ...)
```

Arguments

obj	list(required) : an object of S3 class "mcAgeModels", which is produced by function mcFMM or mcMAM
burn	integer (with default): number of iterations (i.e., the initial, non-stationary portion of the chain) to be discarded
thin	integer (with default): take every thin-th iteration

plot	logical (with default): plot the MCMC output or not
outfile	character (optional): if specified, simulated parameters will be written to a CSV file named "outfile" and saved to the current work directory
...	do not use

Details

Function [reportMC](#) summarizes the output of a Markov Chain (the mean values, the standard deviations, the mode values, and the 2.5, 25, 50, 75, 97.5 quantiles of the simulated parameters). The initial i (burn= i) samples may have been affected by the initial state and has to be discarded ("burn-in"). Autocorrelation of simulated samples can be reduced by taking every j -th (thin= j) iteration ("thinning").

Value

Return a [list](#) that contains the following elements:

pars	means, standard deviations, and modes of simulated parameters
quantile	quantiles of simulated parameters
maxlik	maximum logged likelihood values calculated using the means and modes of simulated parameters
bic	Bayesian Information Criterion (BIC) values calculated using the means and modes of simulated parameters

References

Lunn D, Jackson C, Best N, Thomas A, Spiegelhalter D, 2013. The BUGS book: a practical introduction to bayesian analysis. Chapman & Hall/CRC Press.

Gelman A, Carlin JB, Stern HS, Dunson DB, Vehtari A, Rubin DB, 2013. Bayesian data analysis. Chapman & Hall/CRC Press.

Peng J, Dong ZB, Han FQ, 2016. Application of slice sampling method for optimizing OSL age models used for equivalent dose determination. Progress in Geography, 35(1): 78-88. (In Chinese).

See Also

[mcFMM](#); [mcMAM](#)

SARdata

Data sets used for SAR equivalent dose calculation

Description

SAR data sets for individual aliquots from the "later" group of sample HF11 from Haua Fteah cave, Libya (Li et al., 2016).

Usage

```
data(SARdata)
```

Format

A [data.frame](#) with 840 observations containing the following 5 variables:

NO aliquot (grain) number

SAR.Cycle SAR cycles

Dose regenerative doses

Signal OSL signals

Signal.Err standard error of OSL signals

References

Li B, Jacobs Z, Roberts RG, 2016. Investigation of the applicability of standardised growth curves for OSL dating of quartz from Haua Fteah cave, Libya. *Quaternary Geochronology*, 35: 1-15.

See Also

[fitGrowth](#); [lsNORM](#); [calSGCED](#); [as_analyseBIN](#)

Examples

```
# Not run.  
# data(SARdata)  
# head(SARdata)
```

scaleSGCN

Natural-dose signal re-scaling

Description

Re-scaling sensitivity-corrected natural-dose signals according to the "global standardised growth curve" (gSGC) method suggested by Li et al. (2015, 2016).

Usage

```
scaleSGCN(obj_analyseBIN, SGCpars, model, origin,  
          SAR.Cycle, Tn.above.3BG = TRUE,  
          TnBG.ratio.low = NULL, rseTn.up = NULL,  
          FR.low = NULL, use.se = TRUE, outfile = NULL)
```

Arguments

obj_analyseBIN	list(required) : an object of S3 class "analyseBIN" produced by function analyseBINdata or as_analyseBIN
SGCpars	vector(required) : optimized parameters of the SGC obtained using function fitGrowth or lsNORM
model	character(required) : fitting model used for obtaining SGCpars
origin	logical(required) : logical value indicating if established SGC passes the origin
SAR.Cycle	character(required) : a two-element character vector containing SAR cycles used for natural-dose signal re-scaling. Example: SAR.Cycle=c("N", "R3")
Tn.above.3BG	logical(with default) : logical value indicating if aliquot (grain) with Tn below 3 sigma BG should be rejected
TnBG.ratio.low	numeric(optional) : lower limit on ratio of initial Tn signal to BG
rseTn.up	numeric(optional) : upper limit on relative standard error of Tn in percent
FR.low	numeric(optional) : lower limit on fast ratio of Tn
use.se	logical(with default) : logical value indicating if standard errors of values should be used during application of rejection criteria
outfile	character(optional) : if specified, scaled SGC data related quantities will be written to a CSV file named "outfile" and saved to the current work directory

Details

Sensitivity-corrected natural-dose signals are re-scaled according to **Eqn.(10)** of Li et al. (2015).

Value

Return an invisible [list](#) that contains the following elements:

scale.Ltx	scaled natural-dose signals and associated standard errors
agID	aliquot (grain) ID of scaled natural-dose signals

References

- Li B, Roberts RG, Jacobs Z, Li SH, 2015. Potential of establishing a "global standardised growth curve" (gSGC) for optical dating of quartz from sediments. *Quaternary Geochronology*, 27: 94-104.
- Li B, Jacobs Z, Roberts RG, 2016. Investigation of the applicability of standardised growth curves for OSL dating of quartz from Haua Fteah cave, Libya. *Quaternary Geochronology*, 35: 1-15.

See Also

[lsNORM](#); [calSGCED](#)

Examples

```
# Not run.
data(SARdata)
gSGCpars <- c(137.440874251, 0.007997863, 2.462035263, -0.321536177)
scaleSGCN(as_analyseBIN(SARdata), SGCpars=gSGCpars, model="gok",
          origin=FALSE, SAR.Cycle=c("N", "R3"))
```

sensSAM	<i>Investigate of the sensitivity of a statistical age model to the additional uncertainty (sigmab)</i>
---------	---

Description

Estimate of the parameters of a statistical age model using a number of sigmab values.

Usage

```
sensSAM(EDdata, model, sigmaVEC = NULL, iflog = TRUE,
        maxcomp = 8, plot = TRUE, outfile = NULL)
```

Arguments

EDdata	matrix(required) : a two-column matrix (i.e., equivalent dose values and associated standard errors)
model	character (with default): the fitting model, one of "com", "cam", "mam3", "mam4", "mxam3", "mxam4", "fmm0", "fmm1", "fmm2", ..., "fmm9"
sigmaVEC	vector (with default): a series of sigmab values that will be used as inputs for the model. For example, sigmaVEC=seq(from=0, to=0.3, by=0.01)
iflog	logical (with default): transform equivalent dose values to log-scale or not
maxcomp	integer (with default): the maximum number of components in the FMM
plot	logical (with default): logical value indicating if the results should be plotted
outfile	character (optional): if specified, the results will be written to a CSV file named "outfile" and saved to the current work directory

Value

Return an invisible [list](#) that contains the following elements:

pars	a list that contains the optimized parameters for each sigmab value
mat	a matrix that contains the optimized parameters, the maximum logged likelihood value, and the corresponding Bayesian Information Criterion (BIC) value

References

Peng J, Li B, Jacobs Z, 2020. Modelling heterogeneously bleached single-grain equivalent dose distributions: Implications for the reliability of burial dose determination. *Quaternary Geochronology*, 60: 101108.

Peng J, Li B, Jacobs Z, Gliganic LA, 2023. Optical dating of sediments affected by post-depositional mixing: Modelling, synthesizing and implications. *Catena*, 232: 107383.

See Also

[RadialPlotter](#); [EDdata](#); [optimSAM](#)

Examples

```
# Not run.  
# data(EDdata)  
# sensSAM(EDdata$a13, model="mam4", iflog=TRUE)
```

Signaldata

Decay curves datasets

Description

CW-OSL and LM-OSL decay curves.

Usage

```
data(Signaldata)
```

Format

A list that contains CW-OSL and LM-OSL decay curves:

cw a number of CW-OSL decay curves of a sand sample from the Tengger Desert in northern china (Peng and Han, 2013)

lm a LM-OSL decay curve from Li and Li (2006)

References

Li SH, Li B, 2006. Dose measurement using the fast component of LM-OSL signals from quartz. *Radiation Measurements*, 41(5): 534-541.

Peng J, Han FQ, 2013. Selections of fast-component OSL signal using sediments from the south edge of Tengger Desert. *Acta Geoscientica Sinica*, 34(6): 757-762.

See Also

[decomp](#); [fastED](#)

Examples

```
# Not run.  
# data(Signaldata)  
# names(Signaldata)
```

Index

- * **Alpha dose rate**
 - calDA, 9
- * **Annual dose rate**
 - calDA, 9
- * **BIN file**
 - analyseBINdata, 3
 - BIN, 8
 - loadBINdata, 35
 - numOSL-package, 2
 - pickBINdata, 44
- * **Beta dose rate**
 - calDA, 9
- * **Central Age Model**
 - mcFMM, 39
 - optimSAM, 42
 - RadialPlotter, 49
 - reportMC, 52
 - sensSAM, 56
- * **Cosmic dose rate**
 - calDA, 9
- * **Finite Mixture Age Model**
 - mcFMM, 39
 - optimSAM, 42
 - RadialPlotter, 49
 - reportMC, 52
 - sensSAM, 56
- * **Gamma dose rate**
 - calDA, 9
- * **LS-normalisation**
 - calSGCED, 20
 - lsNORM, 37
 - scaleSGCN, 54
- * **Markov chain Monte Carlo**
 - mcFMM, 39
 - mcMAM, 41
 - reportMC, 52
- * **Maximum Age Model**
 - optimSAM, 42
 - sensSAM, 56
- * **Minimum Age Model**
 - mcMAM, 41
 - optimSAM, 42
 - RadialPlotter, 49
 - reportMC, 52
 - sensSAM, 56
- * **OSL dating**
 - BIN, 8
 - EDdata, 27
 - numOSL-package, 2
 - SARdata, 53
 - Signaldata, 57
- * **batch analysis**
 - calSARED, 18
 - calSGCED, 20
 - numOSL-package, 2
 - pickSARdata, 46
- * **data extraction**
 - calSARED, 18
 - pickBINdata, 44
 - pickSARdata, 46
- * **data importing**
 - loadBINdata, 35
- * **decay curve**
 - decomp, 24
 - fastED, 28
 - numOSL-package, 2
 - Signaldata, 57
- * **dose rate**
 - numOSL-package, 2
- * **equivalent dose**
 - calED, 13
 - calSARED, 18
 - calSGCED, 20
 - dbED, 23
 - EDdata, 27
 - fastED, 28
 - mcFMM, 39
 - mcMAM, 41

- numOSL-package, 2
- optimSAM, 42
- psRadialPlot, 48
- RadialPlotter, 49
- reportMC, 52
- SARdata, 53
- scaleSGCN, 54
- sensSAM, 56
- * **growth curve**
 - analyseBINdata, 3
 - as_analyseBIN, 7
 - calED, 13
 - calRcyRcp, 17
 - calSARED, 18
 - calSGCED, 20
 - fastED, 28
 - fitGrowth, 32
 - lsNORM, 37
 - numOSL-package, 2
 - pickSARdata, 46
 - SARdata, 53
- * **radial plot**
 - psRadialPlot, 48
 - RadialPlotter, 49
- * **statistical age models**
 - mcFMM, 39
 - mcMAM, 41
 - numOSL-package, 2
 - optimSAM, 42
 - RadialPlotter, 49
 - reportMC, 52
 - sensSAM, 56
- analyseBINdata, 3, 4, 6–8, 16, 18, 20, 21, 35, 36, 38, 45–47, 55
- analyseBINdata0 (analyseBINdata), 3
- as_analyseBIN, 7, 7, 18, 21, 46, 54, 55
- BIN, 6, 8, 36, 45
- calDA, 9, 11, 12
- calDAbatch, 11, 12
- calDAbatch (calDA), 9
- calED, 6, 13, 15–18, 20, 22, 29, 31, 35
- calRcyRcp, 16, 17
- calSARED, 6, 7, 16, 17, 18, 22, 35, 47
- calSGCED, 6, 16, 20, 20, 35, 38, 54, 55
- character, 4, 10, 11, 14, 18, 19, 21, 23–25, 29, 32, 35, 37, 42, 44, 46–48, 50, 53, 55, 56
- colors, 23, 48, 50
- data.frame, 5, 7, 8, 36, 47, 54
- dbED, 23, 28, 43, 49, 52
- decomp, 24, 25, 26, 28, 29, 31, 45, 57
- EDdata, 24, 27, 40, 42, 43, 49, 52, 56
- fastED, 16, 17, 27, 28, 29, 35, 45, 57
- fitGrowth, 6, 14–16, 18, 20–22, 29, 31, 32, 33, 37, 38, 46, 47, 54, 55
- integer, 4, 10, 11, 14, 18, 23, 24, 28, 29, 32, 37, 39, 41, 42, 46, 48, 50, 52, 56
- list, 3, 5, 7, 8, 12, 14, 15, 17–19, 21, 23, 24, 26, 28, 30, 33, 34, 36, 38–41, 43–47, 52, 53, 55, 56
- loadBINdata, 6, 8, 35, 35, 44, 45
- logical, 10, 14, 18, 19, 21, 23–25, 28, 29, 32, 35, 37, 39, 41, 42, 45–47, 50, 53, 55, 56
- lsNORM, 6, 21, 22, 35, 37, 38, 47, 54, 55
- matplot, 45
- matrix, 7, 12, 14, 17, 23, 24, 28, 32, 37, 39, 41, 42, 48, 50, 56
- mcCAM (mcFMM), 39
- mcFMM, 28, 39, 40–43, 52, 53
- mcMAM, 28, 40, 41, 43, 52, 53
- nlminb, 50
- numeric, 4, 9, 10, 14, 18, 19, 21, 23, 25, 29, 32, 37, 39, 41, 42, 47, 48, 50, 55
- numOSL-package, 2
- optim, 50
- optimize, 15
- optimSAM, 28, 40, 42, 42, 51, 52, 56
- pickBINdata, 3, 6, 8, 27, 28, 31, 36, 44, 45
- pickSARdata, 6, 7, 17, 20, 35, 46
- psRadialPlot, 24, 28, 43, 48, 48, 52
- RadialPlotter, 24, 28, 40, 42, 43, 49, 49, 50, 56
- reportMC, 40, 42, 52, 53
- SARdata, 7, 22, 35, 37, 38, 53
- scaleSGCN, 22, 38, 54
- sensSAM, 28, 40, 42, 51, 52, 56

Signaldata, [27](#), [31](#), [57](#)

vector, [4](#), [9](#), [14](#), [17](#), [19](#), [21](#), [24](#), [28](#), [29](#), [32](#), [33](#),
[44](#), [45](#), [47](#), [48](#), [50](#), [55](#), [56](#)